

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Tidewater Oil Company (Company or Operator) E. F. King (Lease)
Well No. 5, in SE 1/4 of SW 1/4, of Sec. 1, T. 23S, R. 36E, NMPM.
Langlie Mattix Pool, Lea County.
Well is 660 feet from South line and 1980 feet from West line of Section 1. If State Land the Oil and Gas Lease No. is
Drilling Commenced 1-13, 1960 Drilling was Completed 1-21, 1960
Name of Drilling Contractor Gackle Drilling Co.
Address Box 2076, Hobbs, New Mexico
Elevation above sea level at Top of Tubing Head 3415 The information given is to be kept confidential until
Not Confidential, 19

OIL SANDS OR ZONES

No. 1, from 3715 to 3740 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	22.7	New	373	Texas Pattern	-	-	Surface
5-1/2	15.5	New	3799*	Float	-	3715 - 3740	Oil String
2-3/8	4.7	New	3680				Tubing

*Drilled cement plug to 3797'

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4	8-5/8	373	300	Pump		
7-7/8	5-1/2	3799	500	"		155 bags

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Western Company fraced perfs. 3715-3740' w/ 1000 gal. acid, 10,000 gal. oil & 30,000# sand,
Result of Production Stimulation Flowed 49.5 BO, 4% water in 11 hrs., thru 1/4" choke.
Depth Cleaned Out 3797'