

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 9 feet to 3800 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing January 27, 19 60

OIL WELL: The production during the first 24 hours was 112 barrels of liquid of which 96% was
was oil; 4% was emulsion; % water; and % was sediment. A.P.I.
Gravity 39.0

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen 3670	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	130	130	Surface rock				
130	1015	885	Red bed				
1015	1345	330	Red bed & Anhy.				
1345	1707	362	Anhy.				
1707	2820	1113	Anhy. & salt				
2820	3456	636	Anhy. & gyp.				
3456	3508	52	Anhy.				
3508	3585	77	Anhy. & lime				
3585	3800	215	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

March 25, 1960

(Date)

Company or Operator Tidewater Oil Company

Address Box 547, Hobbs, N. Mex.

Name E. W. Hogue

Position or Title Production Foreman