

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

August 24, 1950

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Place

Date

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company

Mexico "E"

Well No. 1 in S/2 S/2

Company or Operator

Lease

of Sec. 2, T. 23S, R. 36E, N. M., P. M., **Langlie-Mattix** Field, **Lea** County.

The well is 660 feet (N.) (S.) of the South line and 1320 feet (E.) (W.) of the East line of Section 2.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. ? Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is **Skelly Oil Company**Address **Tulsa, Oklahoma**

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary tools from surface to total depth of around 3500'.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12-1/4"	9-5/8"	36	New	1400'	Cemented	600
8-3/4"	7"	20	New	2900'	Cemented	200

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3100 feet.

Additional information: **Halliburton process shall be used in cementing all casing. Cement shall be circulated to surface in cementing 9-5/8" casing.**

Approved Aug. 26, 1950
except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to

Name **Skelly Oil Company**Address **Drawer "D" - Hobbs, New Mexico**

OIL CONSERVATION COMMISSION,

By R. S. BlumTitle **Engineer District I**