

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL OR RECOMPLETE

Notice must be given to the District Office of the Oil Conservation Commission and approval obtained before drilling or recompletion begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in **QUINTUPPLICATE**. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

If State Land submit 6 Copies

Hobbs, New Mexico

(Place)

November 11, 1959

(Date)

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Gentlemen:

You are hereby notified that it is our intention to commence the (Drilling) (~~Recompletion~~) of a well to be known as

Skelly Oil Company

(Company or Operator)

Hobbs "L"

(Lease)

Well No. **1**

"**W**"

(Unit)

located **660** feet from the **South** line and **660'** feet from the **East**

Line of Section **2**, T. **23-S**, R. **36-E**, NMPM.

(GIVE LOCATION FROM SECTION LINE) **Langlie Mattix** Pool, **Lee** County

If State Land the Oil and Gas Lease is No. **B-3776**

If patented land the owner is **-**

Address **-**

We propose to drill well with drilling equipment as follows: **Rotary Tools from surface to total depth.**

The status of plugging bond is **Blanket Bond No. 1253688 for \$100,000.00 with Federal Insurance Co.**

Drilling Contractor **J. C. Crain Drilling Co.**

528 Wilson Building

Dallas, Texas

We intend to complete this well in the **Queen** formation at an approximate depth of **3700'** feet.

CASING PROGRAM

We propose to use the following strings of Casing and to cement them as indicated:

Size of Hole	Size of Casing	Weight per Foot	New or Second Hand	Depth	Sacks Cement
11"	8-5/8"	32#	New	306'	200
7-7/8"	5-1/2"	14#	New	3700'	250

If changes in the above plans become advisable we will notify you immediately.

ADDITIONAL INFORMATION (If recompletion give full details of proposed plan of work.)

The Halliburton Process will be used in cementing both strings of casing and cement will be circulated to surface behind the 8-5/8" OD casing.

Approved _____, 19_____
Except as follows:

Sincerely yours,

Skelly Oil Company

(Company or Operator)

By _____

Position _____

Dist. Supt.

Send Communications regarding well to

Name _____

Skelly Oil Company

Box 38 - Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By _____