

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
N/A 30-025-09234

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

State "A" Account #1

8. Well No.

47

9. Pool name or Wildcat

Langlie Mattix - SR - Qv - GB

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

Clayton W. Williams, Jr., Inc.

3. Address of Operator

6 Desta Drive, Suite 3000, Midland, Texas 79705

4. Well Location

Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

Section 3 Township 23S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3601 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Estimated Start Date: Upon Approval

- 1) Set CIBP @  $\pm 2450'$ . Dump bail 10' of cement on CIBP.  
(2-3/8" tbg fish from  $\pm 2456$  to  $\pm 3556$  prevents setting CIBP deeper)
- 2) Circulate 9.5# gelled brine from CIBP to surface ( $\pm 60$  B)
- 3) Perf 5-1/2" csg @  $\pm 375'$ . Circulate cement to surface down 5-1/2" up 5-1/2/8-5/8 annulus  
( $\pm 125$  sx Class C w/ 2% CaCl<sub>2</sub>)
- 4) Cut 8-5/8" & 5-1/2" csg 3' below GL and set PNA marker in cement.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

David Grafe

TITLE

Petroleum Engineer

DATE

12-8-92

TYPE OR PRINT NAME

David Grafe

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

DEC 09 '92

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

DEC 0 9 1992

ODD NOBIS OFFICE