

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-1506

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR NOTICES TO OIL OR GAS OWNERS OR OILS LACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR PRODUCE FOR SUCH PURPOSES.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- WIW

2. Name of Operator

Atlantic Richfield Company

3. Address of Operator

P. O. Box 1710, Hobbs, New Mexico 88240

4. Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 2310 FEET FROM
THE West LINE, SECTION 3 TOWNSHIP 23S RANGE 36E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Seven Rivers Queen Unit

9. Well No.

47

10. Field and Pool, or without

Langlie Mattix 7R On

11. Elevation (Show whether DF, RT, GR, etc.)

3518' RKB

12. County

Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER Repair Hole in Casing ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

RU 5/9/78. POH w/compl assy. Installed BOP. RIH w/RBP on tbg, set BP @ 3600'. Set pkr @ 400'. Pmpd into csg holes 450-600' w/720# @ 1.5 BPM. POH w/pkr. Spotted 4 sx sd on top of BP (20' sd) Squeezed csg holes 400-800' w/50 sx Calseal followed by 125 sx Cl C cont'g 2% CaCl. MP 1000#. WOC. WIH w/bit to 270', drld hard cmt 270-535'. POH w/bit. Pmpd into holes 400-800' w/1-1/2 BPM @ 750#. Squeezed holes w/125 sx Cl C cmt cont'g 2% CaCl followed by 50 sx Calseal. MP 1000#. WOC. WIH w/bit, drld cmt 403-533'. Fell out of cmt, lowered bit to 700'. Press up on csg & pmpd 1-1/4 BPM @ 850#. Bradenhead squeezed down 5-1/2" csg w/25 sx Calseal followed by 80 sx Cl C cont'g 2% CaCl. Max & final press 1000#. WOC. WIH w/bit, drld good cmt 383-533', fell out of cmt @ 533'. Ran csg scraper to 700'. Pressure tested csg to 1000# 30 mins OK. Washed sd & rec RBP @ 3600'. RIH w/bit, CO hole to 3810' PBD. RIH w/injection assy, Model AD-1 pkr on 2-3/8" IPC tbg w/2 jts TP w/20 alum anodes to 3671'. Set pkr @ 3606'. Circ tbg-csg annulus w/treated FW. Press up csg annulus to 500# 30 mins OK. On 5/29/78 inj 461 BW in 24 hrs, TP 700#, CP 0#. Final Report.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton

TITLE Dist. Drlg. Supt.

DATE 5/31/78

APPROVED BY Jerry Sexton

TITLE

DATE 5/31/78

CONDITIONS OF APPROVAL, IF ANY