

A 10x10 grid with a small rectangle in the top right and a black dot in the bottom right. The rectangle is located in the top right corner, spanning approximately 2 units in width and 3 units in height. The black dot is located in the bottom right corner, at the intersection of the 8th column and 2nd row from the bottom.

APPLICANT

Santa Fe, New Mexico

MONDS OF FIDE QCC

WELL RECORD PM 2:57

PM 2:57

J. F. Janda

(Company or Operator)

(Lease)

Well No. 3, in NE $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 4, T. 23-S, R. 36-E, NMPM.

Cooper Jail

.Pool,

Lea

..County.

Well is 990' feet from East line and 1650 feet from South line

of Section 4 If State Land the Oil and Gas Lease No. is _____

Drilling Commenced April 10, 19 54 Drilling was Completed May 14, 19 54

Name of Drilling Contractor.....Oscar Bourg Drilling Co.

Address.....McClintie Bldg., Midland, Texas

Elevation above sea level at Top of Tubing Head..... 3497' The information given is to be kept confidential until
....., 19.....

No. 1, from 3194' to 3750' No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from.....to..... No. 6, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from to feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
9-5/8"	36#	NEW	467'	Baker			
7"	20#	New	3112'	Baker			

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-1/4"	9-5/8"	482'	360	HOWGO		
8-3/4"	7"	3127'	1300	HOWGO		

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.....

..Depth Cleaned Out.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from surface feet to 3750' feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing May 17, 1954

OIL WELL: The production during the first 24 hours was 76 barrels of liquid of which 100 % was
was oil; 0 % was emulsion; 0 % water; and 0 % was sediment. A.P.I.
Gravity 36.3

GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of
liquid Hydrocarbon. Shut in Pressure _____ lbs.

Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anhy. 1302'
T. Salt 1120'
B. Salt 3030'
T. Yates 3194'
T. 7 Rivers 3464'
T. Queen _____
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Drinkard _____
T. Tubbs _____
T. Abo _____
T. Penn _____
T. Miss _____

T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Farmington _____
T. Pictured Cliffs _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Dakota _____
T. Morrison _____
T. Penn _____
T. _____
T. _____
T. _____
T. _____

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	11.65		Distance from Kelly Drive		3396		Dolomite and Sand
			Bushing to Ground		3423		Dolomite
	105		Caliche and Sand		3533		Dolomite and Sand
	300		Caliche and Red Bed		3587		Dolomite
	490		Red Bed		3750		Dolomite and Sand
	857		Red Bed and Red Rock				
	1103		Sand and Anhydrite				
	1273		Red Bed and Red Rock				
	1357		Anhydrite				
	1557		Anhydrite, Gyp and Salt				
	1825		Anhydrite and Salt				
	2077		Anhydrite				
	2375		Anhydrite and Salt				
	2568		Anhydrite				
	2642		Salt				
	2811		Anhydrite				
	3015		Anhydrite and Salt				
	3142		Anhydrite and Gyp				
	3179		Dolomite and Anhydrite				
	3234		Anhydrite, Dolomite and Sand				
	3253		Lime				
	3287		Sand				
	3340		Sand Stone				
	3356		Sandstone and dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

Company or Operator Gulf Oil Corporation
Name E. F. Taylor

June 2, 1954
(Date)
Address Box 2167, Hobbs, New Mexico
Position or Title Area Prod. Supt.