SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

	October 2			19
Farney 4-5 Well No. 7 is located	990 ft. fr	$rom_{-}\begin{cases} S \\ S \end{cases}$ line ar	nd 165 °C ft. from	line of sec. 5
S#/4 SE/4 Sec. 5 (½ Sec. and Sec. No.)	23-8	36-E	NAPH	,
(1/2 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	*****
NMFU		Lea	New	Mexico
(Field)	(Cou	inty or Subdivision)	(State	or Territory)

The elevation of the derrick floor above sea level is 3469 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Studies performed on this well conclude that remedial work to return the well to a producing status cannot be justified.

We now propose to plug and abandon in the following manner:
1. Set 150' cmt plug (20 ex) from 3800' to 3650'.

Cut & pull approx. 1150° of 5%" casing.

Fill ceg w/10 1b mud and set 20 ex cmt plug at top of 55" ceg.

Set 10 ax cmt plug at surface.

Erect 4" marker extending 4' above surface with well name & location inscribed thereon. Restore location to original condition.

A subsequent report will be filed upon completion of this work.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.				
Company	Continental Oil Company			
	Box 68 - Eunice, New Mexico			
USGS-5 PAN AM CALIF	NMCC-2 ABS FILE -NES-3 ATL-ROSM-2 OIL-HOUS, MID - 1 each	By		

Subject To:

A 100' plug must be placed across the 8 $5/8^{\prime\prime}$ casing shoe, from 238' to 338'.

San Andrew English