Form 9-			,	r Q S			Bureau No. 42-R-355. 1 expires 12-31-55.	3.
	-880	<u></u>	1				LAND OFFICE	
			+]				AL NUMBER LC. BE OR PERMIT TO I	
			+		LIN	ITED STATE	s	
				D		NT OF THE	-	_ }
					GEO	LOGICAL SURV	ΈY	· * * '
		•			-	·····		1
				LOG	OF O	IL OR G	AS WEI	Л.
LOC	CATE WEL	L CORRECTI		200				
_						Box 3908	· •	
						coper-Jal Cou		
ocatic	on 990	ft. N of .	S Line a	nd 1650 ft. []	of E	Line ofSec.		evation
Th	he inform	ation given	herewith is	a complete	and correct	record of the w	ell and all work	done thereon
Date	12-	-253		-	eu		Petroleum Er	
Th	he summe	ry on this p				at above date.		
omme	enced dri	lling 1				d drilling	1-24	, 19_ _53 _
				•	ote gas by G)			
						rom		
,					-	rom		
U. 0, 1				MPORTAN			W	
,			to		No. 3, 1	rom		
o. 2, 1	from		to		No. 4, i G RECOR	rom	to	
Size	Weight per foot	Threads per inch	Make			Cut and pulled from	Perforated	Purpose
5/8	per foot 32	Inch 8	Nat		Larkin		From- To-	0 For product
H-4-0-	15.5	151 11 11 AS	a to a to a to a to	11 3850 c1. pt.	Jenkin un	be a 172 - 1935 - 1 temet a 112 - 1535 - 1 temet a 112 - 1535 - 1535 - 1535 - 1535 - 1535 - 1535 - 1535 - 1535 - 1535 - 1535 - 1535	Praint up	mping or paung.
1917 / 	1632002 1-04-1-6 80	01 (1	31.4 10 150 apr		n changes		-sthraurdenessorie 	าสาสัญญารายฐานตา ปัฐญาราย
			ž 11	NOBY OF	our or c	· · · ·		
			<u></u>					
GH	VIII		Number sacks of cement		Method used Mud gra			
	Where w	et Nur	100	Dem	- 6 - 1	[adm]		•
asing	288 3850		100 275	Pur	p & plug p & plug	(Cemented	cement to s	with 200 sacks
asing	288		275	Pue	p & plug	(Cemented to base o through H	round shoe salt and w illiburton s	with 200 sacks ith 75 sacks tage collar
asing 5/8	288 3850			Pue Pue	nd Adapt	(Cemented to base of through H ERSt 144.0 or	f salt and w salt and w alliburton s r top of sal	with 200 sacks ith 75 sacks tage collar t.
5/8	288 3850 g plug—1	Material	275	Pur PLUGS AN Ler	p & plug ND ADAPT ngth	(Cemented to base o through H	round shoe salt and w alliburton s r top of sal Depth set	with 200 sacks ith 75 sacks tage collar t.
5/8 [eavin, .dapter	288 3850 g plug—1 ers—Mate	Material	None None	Plugs an Plugs an Lei Siz Shooti	ND ADAPT ngth NG RECO	(Cemented to base of through H ERSt 14/.0 of I	round shoe f salt and w alliburton s r top of sal Depth set	with 200 sacks ith 75 sacks tage collar t.
5/8 Jeavin dapter	288 3850 g plug—l rs—Mate	Material	275 Nome Nome Explosive u	PUGS AN PLUGS AN Len Siz SHOOTI sed Qua	P & plug ND ADAPT ngth NG RECO antity Da	(Cemented to base of through H ERSE 142.0 cm I RD e Depth shot	round shoe f salt and w alliburton s r top of sal Depth set	with 200 sacks ith 75 sacks tage collar t.
5/8 5/8 Ieavin dapter	288 3850 g plug—l rs—Mate	Material	275 None Bane Explosive u	PUGS AI PLUGS AI Lei Siz SHOOTI sed Qua guler 155	P & plug ND ADAPT ngth RG RECO antity Da acid from	(Cemented to base of through H ERSt 14/.0 of I RD e Depth shot	round shoe f salt and w alliburton a r top of sal Depth set	with 200 sacks ith 75 sacks tage collar t.
Eaving dapter	288 3850 g plug—1 rs—Mate sh	Material	275 None Bone Explosive u	Plugs An Plugs An Len Siz SHOOTI sed Qua gular 155	P & plug ND ADAPT ngth NG RECO antity Day acid from LS USED	(Cemented to base of through H ERSE 144.0 cm I RD e Depth shot 3772 - 3790	round shoe f salt and w alliburton of r top of sal Depth set	with 200 sacks ith 75 sacks tage collar t.
Size Açidi	288 3850 g plug—1 rs—Mate sh Laed. witt	Material	275 None Explosive us allons re allons contractor	Pur PLUGS AN Len Siz SHOOTI sed Qua gular 155 TOO	P & plug ND ADAPT ngth NG RECO antity Da acid from LS USED 3850 f	(Cement.ed to base of through H ERSE 144.0 cm I RD e Depth shot 3772 - 3790 eet, and from	round shoe salt end w elliburton e r top of sal Depth set Depth c feet t	with 200 sacks ith 75 sacks tage collar t. caned out feet
Leaving dapter Size Açidi	288 3850 g plug—1 rs—Mate sh Laed. witt	Material	275 None Explosive us allons re allons contractor	Plugs An Plugs An Let Siz SHOOTI sed Qua gular 155 TOO feet to fect to	P & plug ND ADAPT ngth NG RECO antity Da acid from LS USED 3850 f	(Cemented to base of through H ERSE 144.0 cm I RD e Depth shot 3772 - 3790	round shoe salt end w elliburton e r top of sal Depth set Depth c feet t	with 200 sacks ith 75 sacks tage collar t. caned out feet
5/8 5/8 [eaving dapter Size Agid1 otary able to Dec	288 3850 g plug—l ms—Mate sh laod wit tools wer ools were cember :	Material en used from used from	275 None Bone Explosive us allons re 0 0 	PUCS AN PLUCS AN Len Siz SHOOTI sed Qua gular 155 TOO feet to feet to D	P & plug ND ADAPT ngth RG RECO Antity Day acid from 1.5 USED 3850 f f ATES Put to p	(Cemented to base of through H ERST 144.0 of I RD e Depth shot 3772 - 3790 eet, and from cet, and from roducing	round shoe salt and w lliburton s r top of sal Depth set Depth definition feet t feet t December 1	with 200 saoks the 75 saoks tage collar t. eaned out 0 feet 0 feet 9 19 53.
Size Agidi Cotary Cable to Dec	288 3850 g plug—1 ers—Mate sh Laod with tools were ools were cember : he produce	Material en used from used from	275 None Explosive u allons re n 0 1953 e first 24 ho	Purs was	P & plug ND ADAPT ngth RG RECO Antity Day acid from 1.5 USED 3850 f f ATES Put to p	(Cemented to base of through H ERST 142.0 of I RD e Depth shot 3772 - 3790 eet, and from roducing s of fluid of whi	round shoe salt and w lliburton s r top of sal Depth set Depth definition feet t feet t December 1	with 200 sacks <u>tage collar</u> t. caned out caned out feet o feet o feet o feet s cil;%
ieaving 5/8 [eaving dapter Sure Açidi otary able to Dec Th mulsio	288 3850 g plug—1 rs—Mate sn sn tools were cember : ne produc on; 75.2 %	Material	275 None Explosive use allons re n 0 n 1953 e first 24 hoo d% see	Plugs An Plugs An Lei Siz SHOOTI sed Qua gular 155 TOO feet to feet to feet to urs was?	P & plug ND ADAPT ngth RC RECO RECO RECO Second From LS USED 3850 f ATES Put to p 250 barrel	(Cemented to base of through H ERST 142.0 of I RD e Depth shot 3772 - 3790 eet, and from roducing s of fluid of whi	round shoe salt and w salt and w salt and w r top of salt Depth set Depth et feet t feet t December 1 ch 24.8% was s 30	with 200 sacks ith 75 sacks tage collar t. caned out 0feet 0feet 9feet 9feet 9feet 9feet
5/8 5/8 [eavin] dapter Size Açidi otary able to Dec Th mulsio If g	288 3850 g plug—l rs—Mate sn Lsed witt tools were cools were cools were cools were cools were cools were cools were cools were cools were	Material	275 None Explosive u ellons re n 0 , 1953 e first 24 ho d% see 24 hours	Plugs An Plugs An Lei Siz SHOOTI and qua gular 155 TOO feet to feet to urs was diment.	p & plug ND ADAPT ngth NG RECO NG	(Cemented to base of through H ERST 14/0 of I RD e Depth shot 3772 - 3790 eet, and from eet, and from roducing s of fluid of whi Gravity, °Bd	round shoe salt and w salt and w salt and w r top of salt Depth set Depth et feet t feet t December 1 ch 24.8% was s 30	with 200 sacks ith 75 sacks tage collar t. caned out 0feet 0feet 9feet 9feet 9feet 9feet
5/8 5/8 6 6 6 7 8 8 7 8 7 8 7 8 7 8 7 8 7 8 7	288 3850 g plug—1 rs—Mate sn sn sols were cember : ne produc on; 75.2 % gas well, ock pressu	Material	275 None Explosive u ellons re n 0 1953 e first 24 hou d% see 24 hours	Plugs An Plugs An Lei Siz SHOOTI sed Qua gular 155 feet to feet to feet to urs was feet to b urs was feet to feet to	P & plug ND ADAPT ngth NG RECO NG RECO NG NG RECO NG RECO NG RECO NG RECO NG RECO NG RECO NG RECO S NG RECO S NG RECO S NG RECO S S NG RECO S S S S S S S S	(Cemented to base of through H ERST 14/0 of I RD e Depth shot 3772 - 3790 eet, and from eet, and from roducing s of fluid of whi Gravity, °Bd	round shoe salt and w salt and w salt and w salt and w r top of salt Depth set Depth ef feet t feet t December 1 ch 24.8% was s. 30 0 cu. ft. of gas	with 200 sacks tege collar t. caned out 0 feet 0 feet 0 feet 0 feet 0 feet
Sise Acid1 Cotary Cable to Dec If g	288 3850 g plug—l rs—Mate sh Lsed witt tools were ools were comber : he produc on;75.2% gas well, ock pressu J.	Material	275 None Explosive u allons re n 0 , 19 53 e first 24 ho d% see 24 hours	PluGS AN PLUGS AN Len Siz SHOOTI sed Qua guler 155 TOO feet to feet to urs was diment. EMF , Driller	PA Plug ND ADAPT ngth NG RECO NG RECO Satury Dat acid from f ATES Put to p 250 barrel Callons g PLOYEES	(Cemented to base of through H ERST 144.0 of Pepth shot 3772 - 3790 et, and from pet, and from roducing s of fluid of whi Gravity, °Bo asoline per 1,00 H. R. 1	round shoe salt and w salt and w salt and w r top of salt Depth set Depth e feet t feet t December 1 ch 24.8% was s. 30 0 cu. ft. of gas Mitchell	with 200 sacks tage collar t. caned out 0 feet 0 feet a oil;
Size Acidi Cotary Cable to Dec Th mulsio If g Ro	288 3850 g plug—l rs—Mate sh Laed witt tools were ools were cember : he produc on; 75.2 % gas well, ock pressu J. R.	Material orial en used it 1000 gr re used from used from - 1, tion for the 6 water; and cu. ft. per 2 ure, lbs. per L. Lewis Dunlap	275 None Explosive u allona re allona re allona se first 24 ho d% see 24 hours	PluGS AN PLUGS AN Len Siz SHOOTI red Qua gular 15% TOO feet to feet to feet to D urs was Len FormAT	P & plug ND ADAPT ngth NG RECO NG RECO NG RECO Data Solution Gallons g COYEES	(Cemented to base of through H ERST 144.0 of Pepth shot 3772 - 3790 eet, and from reducing s of fluid of whi Gravity, °Bd asoline per 1,00 R. R. 1 RD	round shoe f salt and w alliburton a r top of sal Depth set Depth e feet t feet t December 1 ch 24.8% was s. 30 0 cu. ft. of gas Kitchell	with 200 sacks tage collar t. caned out 0 feet 0 feet a oil;
eising 5/8 Heaving Idapter Size Agidi Rotary Cable to Dec Th mulsio If g Ro	288 3850 g plug—l rrs—Mate sh Laed witt tools were ools were cember : he produc on; 75.2 % gas well, ock pressu J. R.	Material en used it 1000 gr re used from used from - 1, tion for the 6 water; and cu. ft. per 2 ire, lbs. per L. Lewis Dunlap TO-	275 None Explosive u allona re allona re allona se first 24 ho d% see 24 hours	PUCS AN PLUCS AN Len Siz SHOOTI wed Quar gular 15% TOOP feet to feet to feet to D urs was EMF , Driller FORMAT DTAL FEET	P. & plug ND ADAPT ngth NG RECO NG RECO NG RECO Sanutry Dat acid from (Satis USED 3850 f partes Put to p 250 barrel Gallons g COYEES	(Cemented to base of through H ERST 144.0 of Pepth shot 3772 - 3790 eet, and from roducing s of fluid of whi Gravity, °Bo asoline per 1,00 H. R. 1 RD	round shoe f salt and w alliburton a r top of salt Depth set Depth e feet t feet t December 1 ch 24.8% was s. 30 0 cu. ft. of gas Kitchell	with 200 sacks tage collar t. caned out 0 feet 0 feet a oil;
eising 5/8 Heaving Idapter Acidi Cable to Dec Th mulsio If g Ro FRO 0 250	288 3850 g plug—l rs—Mate sh Laed witt tools were ools were cember : he produc on,75.2 gas well, ock pressu J. R.	Material orial en used it 1000 gr re used from used from . 1, tion for the 6 water; and cu. ft. per 2 ure, lbs. per L. Lewis Dunlap TO- 250 1435	275 None Explosive u allona re allona re allona se first 24 ho d% see 24 hours	PluGS AN PLUGS AN Len Siz SHOOTI sed Qua gular 155 TOO feet to feet to feet to Urs was? diment. EMF , Driller FORMAT DTAL FEET 250 1185	P. & plug ND ADAPT ngth NG RECO NG RECO NG RECO Sanutry Dat acid from (Satis USED 3850 f partes Put to p 250 barrel Gallons g COYEES	(Cemented to base of through H ERST 144.0 of Pepth shot 3772 - 3790 eet, and from reducing s of fluid of whi Gravity, °Bd asoline per 1,00 R. R. 1 RD	round shoe f salt and w alliburton a r top of salt Depth set Depth e feet t feet t December 1 ch 24.8% was s. 30 0 cu. ft. of gas Kitchell	with 200 sacks tage collar t. caned out 0 feet 0 feet a oil;
Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Leaving Lea	288 3850 g plug—1 rs—Mate sh Lsed witt tools were comber : ne produc on;75.2% gas well, ock pressu J. R.	Material orial en used it 1000 gr re used from used from . 1, tion for the 6 water; and cu. ft. per 2 ure, lbs. per L. Lewis Dunlap TO- 250	275 None Explosive u allona re allona re allona se first 24 ho d% see 24 hours	PluGS AN PLUGS AN Len Siz SHOOTI sed Qua gular 155 TOO feet to feet to urs was? diment. Driller FORMAT PLUGS AN Qua Siz SHOOTI PLUGS AN Qua Siz SHOOTI PLUGS AN Qua Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SHOOTI Siz SIZ SHOOTI Siz SIZ SIZ SIZ SIZ SIZ SIZ SIZ SIZ	PA Plug ND ADAPT ngth NG RECO NG RECO SUSED 3850 f Put to p 250. barrel Gallons g PLOYEES ION RECO	(Cement.ed to base of through H ERST 144.0 of Pepth shot 3772 - 3790 e Depth shot 3772 - 3790 eet, and from pet, and from roducing s of fluid of whi Gravity, °B asoline per 1,00 H. R. 1 RD FOR Band and graves	round shoe f salt and w alliburton a r top of salt Depth set Depth e feet t feet t December 1 ch 24.8% was s. 30 0 cu. ft. of gas Kitchell	with 200 sacks tage collar t. caned out 0 feet 0 feet a oil;
Sise Agidi Cotary Sable to Dec Th mulsio If a Ro FBO	288 3850 g plug—1 rs—Mate sh Laed. witt tools were cember : ne produc on;75.22 gas well, ock pressu J. R.	Material en used it 1000 gr re used from used from . 1, tion for the 6 water; and cu. ft. per 2 ire, lbs. per L. Lewis Dunlap TO- 250 1435 1560	275 None Explosive u allona re allona re allona se first 24 ho d% see 24 hours	PluGS AN PLUGS AN Len Siz SHOOTI sed Qua gular 155 TOO feet to feet to feet to Urs was? diment. EMF , Driller FORMAT DTAL FEET 250 1185	P. & plug ND ADAPT ngth NG RECO NG RECO Antity Day acid from LS USED 3850 f ATES Put to p 250 barrel Gallons g LOYEES ION RECO Surface Red bed Anhydri Salt Dolomit	(Cement.ed to base of through H ERST 144.0 of Pepth shot 3772 - 3790 e Depth shot 3772 - 3790 eet, and from pet, and from roducing s of fluid of whi Gravity, °B asoline per 1,00 H. R. 1 RD FOR Band and graves	round shoe f salt and w alliburton a r top of sal Depth set Depth e feet t feet t December 1 ch 24.8% was 30 0 cu. ft. of gas Kitchell MATION avel	with 200 sacks tage collar t. caned out 0 feet 0 feet a oil;

FOLD MARK



. '

l

1

1

FROM	то	TOTAL FEET	FOBMATION	1
、				
4		T	· · · · · · · · · · · · · · · · · · ·	
- - -				
-		-		
	18 A.			
	· ·			
			1 · C	
		- · · ·		913 A
•••	•	$V_{i,j}^{(i)} \in J$	•	5 · · · · II'
-•1,	- · ·	2 		
· · };			(
			• • • •	
				.,
e 1. j				: •
				- foc b
		· ·		
		•	· · · ·	-
,	~~	· · ·		* •••
			1 total and	
	, tri i s			
1 7 1 -	-11: .71;			-
	- ¹ -			مراجعات الم مراجعات الم
	Г' ''	1 . *	b b b b b b b b b b	-

FORMATION RECORD-Continued

HISTORY OF OIL OR GAS WELL

ί

ί.

10-48094-2 U. S. GOVERNMENT PRINTING OFFICE

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrifting, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plags or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing. <u>.</u> . - -