

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-09287
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name State A A/C 1
8. Well No. 10
9. Pool name or Wildcat Jalmat TNSL-YTS-SR

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator Clayton W. Williams, Jr., Inc.
3. Address of Operator Six Desta Drive, Suite 3000 Midland, Texas 79705	4. Well Location Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line Section 9 Township 23S Range 36E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3500 GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/17 to 12/28/92

1) CIBP set @ 3460' w/34' of cement on plug on 12/89.

2) Circulated 10# gelled brine from CIBP to surface.

3) Perforated 5-1/2" csg @ 500', 2 SPF. Pumped 325 sx Class "C" cement w/2% CaCl2 down 5-1/2" casing and up 5-1/2", 10" annulus. Circulated 5 sx to surface.

4) Cut 10" and 5-1/2" csg 3' below GL and welded on PNA marker. Cut all anchors 3' below GL. Cleaned location.

See Attached Wellbore Diagram

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Petroleum Engineer

DATE 01/06/93

TYPE OR PRINT NAME

David Grafe

TELEPHONE NO 682-6324

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OIL & GAS INSPECTOR

JAN 21 1993