



AREA 640 ACRES  
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

OFFICE 000

WELL RECORD 1862 552 18 AM 10:03

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Texas Pacific Coal and Oil Company  
(Company or Operator)

State "A" A/e-1  
(Lease)

Well No. 41, in 1/4 of 1/4, of Sec. 10, T. 23-S, R. 36-E, NMPM.

Langlin-Kettix Pool, Lea County.

Well is 660 feet from North line and 1980 feet from East line

of Section 10. If State Land the Oil and Gas Lease No. is 35-24

Drilling Commenced January 2, 1960. Drilling was Completed January 28, 1960

Name of Drilling Contractor F. W. A. Drilling Company J. P. Gibbins, Inc.

Address Wichita Falls, Texas Midland, Texas

Elevation above sea level at Top of Tubing Head 3486. The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3671 to 3754 RTH No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
9-5/8	31	New	316	Float			Surface
7	20	New	3671	Float			Production String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
14	9-5/8	346	300 #15 Oil	Pump & Plug		
8-3/4	7	3681	250 #15 Oil	Pump & Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Open hole Fibre-Frased at 3725-50' w/2 lbs. 5 charges.

30T w/10,000 gal. refined oil & 10,000 lbs. 20/40 sand.

Result of Production Stimulation Flowed 14 bbls. oil, 7.5 bbls. water through a 20/64" choke in 8 hrs. tested on 4/9/60.

Depth Cleaned Out 3754 RTH

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3754 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing February 3, 1960

OIL WELL: The production during the first 24 hours was 149.3 barrels of liquid of which 94.9% was oil; 0% was emulsion; 2.1% water; and 0% was sediment. A.P.I. Gravity 35

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.  
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1277		T. Devonian		T. Ojo Alamo
T. Salt.	1494		T. Silurian		T. Kirtland-Fruitland
B. Salt.	2777		T. Montoya		T. Farmington
T. Yates	3100		T. Simpson		T. Pictured Cliffs
T. 7 Rivers	3304		T. McKee		T. Menefee
T. Queen	3737		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash.		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	100	100	Sand				
100	430	330	Red Sand				
430	1157	727	Red Sand & Shale				
1157	2035	1878	Anhyd. & Salt				
2035	3225	1190	Anhyd. & Gyp.				
3225	3669	444	Lime				
3669	3754	85	Lime & Sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

February 16, 1960

Company or Operator Texas Pacific Coal & Oil Company Address P. O. Box 1408, El Paso, New Mexico  
Name [Signature] Position Title Petroleum Engineer