

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.


Hobbs, New Mexico  
PlaceOctober 3, 1949  
DateOIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Gulf Oil Corp. - Gypsy Prod. Division J. F. Janda "H" Well No. 1 in NE SE  
Company or Operator Lease

of Sec. 11, T. 23S, R. 36E, N. M. P. M. Langlie Mattix Field, Lea County.



AREA 640 ACRES

LOCATE WELL CORRECTLY

The well is 1980 feet (N.) 850 of the south line and 660 feet (W.) of the east line of Section 11

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is Mr. Matkins

Address Carlsbad, New Mexico

If government land the permittee is

Address

The lessee is Gulf Oil Corp. - Gypsy Production Division

Address Box 661, Tulsa, Oklahoma

We propose to drill well with drilling equipment as follows:

Rotary tools

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12 1/4"	9 5/8"	36#	New	300'	Cemented	300
7 3/8"	5 1/2"	11#	New	3000'	Cemented	See note

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3,000 feet.

Additional information: Note: 5 1/2" casing to be cemented with Halliburton D.V. two stage cementing tool set on top of the salt section. First stage cemented with 750 sacks  
Second stage cemented with 125 sacks

Approved \_\_\_\_\_, 1949  
except as follows:

Sincerely yours,

Gulf Oil Corp. - Gypsy Production Division  
Company or Operator

By

E. J. Gallagher

Position District Superintendent

Send communications regarding well to

Name E. J. Gallagher

Address Box 1667, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,  
By Roy D. Yunkrough  
Title OIL & GAS INSPECTOR