| | UNLED STATE DEPARTMENT OF THE BUREAU OF LAND MANA | INTERIOR N. | reach Dr. M 88240 | 5. Lease Seri | FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000 al No. | |
|---|---|--|--|---|--|-----------------|
| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. | | | | LC030556B 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or N 8. Well Name and No. Stevens B No. 8 | | |
| | | | 6. If Indian, A | | | |
| SUBMIT IN TRIPLICATE - Other instructions on reverse side | | | | | | 7. If Unit or (|
| Type of Well Oil Well Gas Well Other Salt Water Disposal | | | | | | |
| 2. Name of Operator John H. Hendrix Corporation | | | | | 9. API Well No. | |
| 3a. Address P. O. Box 3040, Midland TX 79702-3040 4. Location of Well (<i>Footage, Sec., T., R., M., or Survey Descripti</i> UL: A, 660' FNL & 660' FEL, Sec. 12, T23S, R36 | | | | | 30-025-09329 | |
| | | | | 10. Field and Pool, or Exploratory Area Langlie Mattix 7 Rvr. | | |
| | | | | 11. County or Parish, State Lea County, NM | | |
| 12. CHECK A | PPROPRIATE BOX(ES) T | O INDICATE NA | TURE OF NOTICE | , REPORT, OR | OTHER DATA | |
| TYPE OF SUBMISSION | | TYPE OF ACTION | | | | |
| □ Notice of Intent | Acidize | Deepen | Production (S | Start/ Resume) [| Water Shut-Off | |
| - | Alter Casing | Fracture Treat | Reclamation | [| Well Integrity | |
| X Subsequent Report | Casing Repair Change Plans | New Construction | | | Other Casing Int Test | |
| Final Abandonment Notice | Convert to Injection | Plug Back | Water Dispos | | | |
| Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. | ocations measured and tr file with BLM/BIA. Req completion or recompleti | ue vertical depths o uired subsequent re ion in a new interval | f all pertinent markers and zor ports shall be filed within 30 , a Form 3160-4 shall be filed | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Test | ue vertical depths o uired subsequent re- ion in a new interval clamation, have been clamation, have been clamatio | f all pertinent markers and zor ports shall be filed within 30 I, a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked on disposal. | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Tes edy Gonzales to w | ue vertical depths o uired subsequent re- ion in a new interval clamation, have been clamation, have been clamatio | f all pertinent markers and zor ports shall be filed within 30 I, a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Tes edy Gonzales to w | ue vertical depths o uired subsequent re- ion in a new interval clamation, have been clamation, have been clamatio | f all pertinent markers and zor ports shall be filed within 30 I, a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked on disposal. | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Tes edy Gonzales to w | ue vertical depths o uired subsequent re- ion in a new interval clamation, have been clamation, have been clamatio | f all pertinent markers and zor ports shall be filed within 30 d , a Form 3160-4 shall be filed n completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of char | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked on disposal. "t attached. Original sent | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesitt to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Te edy Gonzales to w ylvia Dickey. | ue vertical depths o uired subsequent re- ion in a new interval clamation, have been clamation, have been clamatio | f all pertinent markers and zor ports shall be filed within 30 I, a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of char | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked on disposal. "t attached. Original sent | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesit to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe t to OCD, Attn: S | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Te edy Gonzales to w ylvia Dickey. | ue vertical depths o uired subsequent re- ion in a new interval clamation, have been clamation, have been clamatio | f all pertinent markers and zor ports shall be filed within 30 I, a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of chan I4. Thereby certify that the foreg Name (<i>Printed/Typed</i>) Ronnie H. Westbrook | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH v psig in 30 mins. Talked on disposal. t attached. Original sent | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe t to OCD, Attn: S Titl Vic Dat 02, | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Tes edy Gonzales to w ylvia Dickey. | ue vertical depths o puired subsequent re- ion in a new interval clamation, have beer clamation, have beer clamati | f all pertinent markers and zor ports shall be filed within 30 I, a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of char 14. I hereby certify that the foreg Name (<i>Printed/Typed</i>) Ronnie H. Westbrook | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) thermined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH y psig in 30 mins. Talked on disposal. t attached. Original sent oing is true and correct | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe t to OCD, Attn: S | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Tes edy Gonzales to w ylvia Dickey. | ue vertical depths o puired subsequent re- ion in a new interval clamation, have beer clamation, have beer clamati | f all pertinent markers and zor ports shall be filed within 30 , a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of .1/2" annulus to | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of char 14. I hereby certify that the foreg Name (<i>Printed/Typed</i>) Ronnie H. Westbrook | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) thermined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH y psig in 30 mins. Talked on disposal. t attached. Original sent oing is true and correct | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe t to OCD, Attn: S | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec sg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Tes edy Gonzales to w ylvia Dickey. | ue vertical depths o puired subsequent re- ion in a new interval clamation, have beer clamation, have beer clamati | f all pertinent markers and zor ports shall be filed within 30 , a Form 3160-4 shall be filed n completed, and the operator 0 to 775'. Fell out of -1/2" annulus to ed results of test. Test | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of chan See copy of chan I4. I hereby certify that the foreg Name (<i>Printed/Typed</i>) Ronnie H. Westbrook Signature ACCEPTED FC Approved by ORIG. SGD.) Conditions of approval, it any, an certify that the applicant holds leg | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) termined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH w psig in 30 mins. Talked on disposal. t attached. Original sent oing is true and correct DR RECOMMENT DR RECOMMENT Space 5-2003 - 2003 - 2003 - 2004 - 2005 - 200 | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe t to OCD, Attn: S Titl Vic Dat 602 FOR FEDERAL O | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec esses would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Ter edy Gonzales to w ylvia Dickey. | ue vertical depths o pured subsequent re- ion in a new interval clamation, have beer clamation, have beer clamatio | f all pertinent markers and zor ports shall be filed within 30 , a Form 3160-4 shall be filed n completed, and the operator 0 to 775'. Fell out of -1/2" annulus to ed results of test. Test | |
| If the proposal is to deepen di Attach the Bond under which following completion of the i testing has been completed. F determined that the site is rea 2/5/03 Using packer de 2/6/03 Squeezed 4-1/2 2/7/03 Drld. cement fr. 2/8/03 Drld. cement fr. 2/10/03 Spot cement fr. 2/11/03 Drld. cement fr. 2/11/03 Drld. cement fr. 2/13/03 Circ. annulus w/ 540' psig. Tested to 535 approved by OCD to put See copy of chan See copy of chan I4. I hereby certify that the foreg Name (<i>Printed/Typed</i>) Ronnie H. Westbrook Signature ACCEPTED F(Approved by ORIG. SGD.) | rectionally or recomplete horizon the work will be performed or pr nvolved operations. If the operati inal Abandonment Notices shall dy for final inspection.) thermined leaks between " csg. w/ 200 sx. Class C 240 - 457'. 457' to 498'. Fell out of c 781' to surface. Obtaine 240 to 550'. Tested csg. 42 bbls. pkr. fluid. RIH y psig in 30 mins. Talked on disposal. t attached. Original sent original sent original sent conduct operations thereon. di Approval of this nor gal or equitable title to those right to conduct operations thereon. di Approval of this nor gal or equitable title to those right to conduct operations thereon. | ovide the Bond No. on on results in a multiple be filed only after all re 445' & 630'. cement at 498'. C d 1000 psig hesita to 600 psig - no l w/ 4-1/2" AD-1 pk to OCD Rep Spe t to OCD, Attn: S Titl Vic Dat FOR FEDERAL O | ocations measured and tr file with BLM/BIA. Req completion or recompleti quirements, including rec seg. would not test. ation squeeze. leak off. Cont. drlg r. set at 3590'. Ter edy Gonzales to w ylvia Dickey. | ue vertical depths o puired subsequent re- ion in a new interval clamation, have beer i. cement fr. 55 sted 2-3/8" x 4- itness. Report | f all pertinent markers and zor ports shall be filed within 30 , a Form 3160-4 shall be filed a completed, and the operator 0 to 775'. Fell out of -1/2" annulus to ed results of test. Test | |

