

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on plugging and abandoning well.	X

April 25, 1949
Date

Hobbs, New Mexico
Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Gulf Oil Corporation J. F. Janda "E" Well No. 2 in the

Company or Operator

Lease

NE/4 of Sec. 21, T. 23S, R. 36E, N. M. P. M.,

Lynn Field, Lea County.

The dates of this work were as follows: Started April 16, 1949. Completed April 23, 1949.

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on January 27, 1949 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran tubing to 3415' and mudded hole to surface. Spotted 5 sacks of cement @ 2800' and pulled tubing. Shot 5½" casing off @ 2100', and recovered 2086' (87 jts.). Ran tubing to 2075', mudded hole to surface, and spotted ten sacks of cement @ 2075'. Shot 7-5/8" @ 1950', 1850', 1750', 1530', 1450', 1350', 1250', 1150', 1050', 900', 800', 700', 600', 550', and 470'. Recovered 470' (21 jts.) of 7-5/8" casing. Ran tubing to 470', mudded hole to surface, spotted 6 sacks of cement in top of 10-3/4" casing, pulled tubing, and set regulation marker on surface.

Witnessed by C. C. Brown Gulf Oil Corporation Production Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

25th day of April 1949

Name *D. J. Gallagher*

Position District Sup't.

Representing Gulf Oil Corporation
Company or Operator

C. C. Brown
Notary Public

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks:

W. C. [Signature]
Name

Title