

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Supersedes OIM
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE MAPS AND RECORDS FOR THESE TYPES OF OPERATIONS.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Grace Petroleum Corporation

Address of Operator

P. O. Drawer 2358, Midland, Texas 79702

Location of Well

UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 22 TOWNSHIP 23-S RANGE 36-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

3391' DF

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-934

7. Unit Agreement Name

8. Name of Lease Name

New Mexico "AA" State

9. Well No.

5

10. Field and Pool, or Wildcat

Langlie-Mattix

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

WELL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

1. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 5-11-79 MIRUPU. RIH w/WL CIBP & set @ 3650'. RIH w/1½" tbg & spotted 4 sx cmt plug on top of CIBP. POH w/1½" tbg. Cut 2 7/8" csg @ 2600' & POH LD 84 jts. RIH w/1½" tbg & spotted 25 sx cmt plug from 2600' up. Pulled up above plug w/tbg & SDON.
- 5-12-79 RIH to tag plug. No fill. Spotted 25 sx cmt plug from 2600' up. Pulled up above plug w/tbg & shut down for weekend.
- 5-14-79 RIH w/1½" tbg & tagged plug (100' fill). Circ'd hole w/mud laden fluid. Picked up tbg & spotted 25 sx cmt plug across 7" surface csg shoe @ 336'. SDON.
- 5-15-79 RIH to tag plug. No fill. Pumped mud containing loss circulation material down tbg & then spotted 35 sx cmt plug across 7" surface csg shoe. WOC 4 hrs. Tagged top of cmt @ 170' FS inside 7" csg. Spotted 15 sx cmt @ surface. Cut-off well-head & installed marker. RDMOPU.

I, Thereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Douglas W. Rice

TITLE Assistant District Prod. Manager DATE 5-24-79

APPROVED BY [Signature]

OIL & GAS INSPECTOR

DATE NOV 18 1979

CONDITIONS OF APPROVAL, IF ANY

RECEIVED

MAY 25 1979

**OIL CONSERVATION COMM.
HOBBS, N. M.**