


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Gulf Oil Corporation Box 661 Tulsa 2, Oklahoma
Company or Operator Address
Alice Paddock Well No. 4 in NE/4 of Sec. 1, T. 22S
Lease
R. 37E N. M. P. M. Paddock Field, Lea County.
Well is 1980 feet south of the North line and 1980 feet west of the East line of NE/4
If State land the oil and gas lease is No. - Assignment No. -
If patented land the owner is - Address -
If Government land the permittee is - Address -
The Lessee is Gulf Oil Corporation Address Tulsa, Oklahoma
Drilling commenced January 22 1946 Drilling was completed February 26 1946
Name of drilling contractor Parker Drilling Company Address Tulsa, Oklahoma
Elevation above sea level at top of casing 3358 feet. Derrick floor.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from Pay 5200 to 5227 No. 4, from - to -
No. 2, from - to - No. 5, from - to -
No. 3, from - to - No. 6, from - to -

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from - to - feet.
No. 2, from - to - feet.
No. 3, from - to - feet.
No. 4, from - to - feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
13-3/8	48	8R	Smls	298'					
9-5/8	36	8R	E W	2955'					
7	23	8R	E W	5263'			5197	5227	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/4	13-3/8	298	300	HOWCO		
12-1/4	9-5/8	2955	1300	HOWCO		
8-3/4	7"	5263	450	HOWCO		

PLUGS AND ADAPTERS

Heaving plug—Material - Length - Depth Set -
Adapters—Material - Size -

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	1000	3-4-46		
		Acid	2000	3-7-46		

Results of shooting or chemical treatment -

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5263' feet, and from - feet to - feet
Cable tools were used from - feet to - feet, and from - feet to - feet

PRODUCTION

Put to producing March 7 1946
The production of the first 24 hours was 172 barrels of fluid of which 95% was oil; -% emulsion; 5% water; and -% sediment. Gravity, Be 380
If gas well, cu. ft. per 24 hours - Gallons gasoline per 1,000 cu. ft. of gas -
Rock pressure, lbs. per sq. in. -

EMPLOYEES

Parker Drilling Company Driller - Driller -
Driller - Driller -

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 22ndday of April 19 46H. W. Evans
Notary PublicMy Commission expires March 16, 1948

Tulsa, Oklahoma April 22, 1946

Name A. M. Bell, Jr.Position General SuperintendentRepresenting Gulf Oil Corporation
Company or OperatorAddress Box 661, Tulsa 2, Oklahoma

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	15		Floor to cellar
	325		Surface hole
	389		Red bed shale & shells
	655		Red bed shale
	773		Red rock & shells
	883		Red bed and shells
	976		Shale and shells
	1087		Red rock & shale
	1192		Red bed & shells
	1232		Red bed shale
	1240		Shale and shells
	1291		Anhy. & red rock
	1311		Anhy. & gyp
	1372		Anhy. red bed & shells
	1502		Salt and shells
	1564		Salt & potash & gyp
	1740		Anhy. & salt brakes
	1835		Anhy. & salt
	2331		Anhy. & salt brakes
	2429		Salt
	2558		Anhydrite
	2607		Anhydrite & gyp
	2818		Anhydrite
	2832		Red bed shell
	2980		Anhydrite
	3005		Sand
	3058		Anhy. & sand
	3165		Anhy. & shale
	3245		Anhy. & lime shells
	3293		Shale & shells & lime
	3553		Anhy. & lime
	3597		Shale, lime & sand
	3672		Lime
	3708		Anhy. & lime
	3771		Shale and lime
	4283		Lime
	4651		Lime sandy
	4689		Lime
	4742		Sandy lime
	4794		Lime
	4852		Broken sandy lime
	5245		Lime
	5263		Lime TOTAL DEPTH

ED
4-22-46