Form C-102 NE\ AEXICO ØIL CON Santa Fe,	New Mexico
	EOUS NOTICES MAR 19 1941
to begin. A copy will be returned to the sender on which	Commission or its proper agent bifford the workprocified is chosen will be given the approval, with any modifications cont
be followed, and work should not begin until approval	r agent, of the plan submitted. The plan as approved should I is obtained. See additional instructions in the Rules and
Regulations of the Commission.	- the dealer below
Indicate nature of n NOTICE OF INTENTION TO TEST CASING	NOTICE OF INTENTION TO SHOON OR WITH AND
SHUT-OFF I	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PUBLIOR OTHERWISE ALTER CASING/ MAR 1'7 1941
NOTICE OF INTENTION TO REPAIR WELL	
NOTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PERSONNELL SUV
	Diessa Texas S-15-41. Place Date
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico	
Gentlemen: Following is a notice of intention to do certain work as a	described below at the
Parker Drilling Co. State	"C" Well No. 1 in S.W.Cor.
Company or Operator Lease	
of Sec. 2, T. 22, R. 37	, N. M. P. M., Penrose Field,
County	
County.	
FULL DETAILS OF PR	
FOLLOW INSTRUCTIONS IN THE RULES	S AND REGULATIONS OF THE COMMISSION
	S AND REGULATIONS OF THE COMMISSION
Set & Cemented 115 jts.3592' of 5	s and regulations of the commission
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Matl.Tube casing Using 200 sks. 0	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 8rd. thrd. new 5 El. Toro Cement Halliburton'system 5 7:30 A.M. 3-11-41 set 72 hrs. Plug
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15 Grade H-40 8rd. thrd. new 0 Kl. Tore Cement Halliburton'system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K.
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1	S AND REGULATIONS OF THE COMMISSION
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved 19	s AND REGULATIONS OF THE COMMISSION 5 0.D. 15 Grade H-40 8rd. thrd. new 0 Kl. Tore Cement Halliburton'system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K.
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved 19	S AND REGULATIONS OF THE COMMISSION
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved 19	S AND REGULATIONS OF THE COMMISSION S O.D. 15# Grade H-40 Srd. thrd. new Of El. Tore Gement Halliburton'system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K. Parker Drilling Co. Company or Operator W.E.Snell By
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved 19	S AND REGULATIONS OF THE COMMISSION State of the common the set of the system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested O.K. Parker Drilling Co. Company or Operator By
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved 19 except as follows:	S AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 Srd. thrd. new 5 X1. Tore Cement Halliburton'system 5 7:30 A.M. 5-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K. Parker Drilling Co. Company or Operator By
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. O Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1	S AND REGULATIONS OF THE COMMISSION S O.D. 15# Grade H-40 Srd. thrd. new S XI. Tore Cement Halliburton'system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K. Parker Drilling Co. Company or Operator W.E.Snell By
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 aks. 0 Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved	S AND REGULATIONS OF THE COMMISSION 5 0.D. 15# Grade H-40 Srd. thrd. new 5 X1. Tore Cement Halliburton'system 5 7:30 A.M. 5-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K. Parker Drilling Co. Company or Operator By
Set & Cemented 115 jts.3592' of 5 Natl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved 19 except as follows:	S AND REGULATIONS OF THE COMMISSION S O.D. 15# Grade H-40 Srd. thrd. new S X1. Toro Cement Helliburton'system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested O.K. A.M. S-11-41 set 72 hrs. Plug hr. baler method. Tested O.K. Supt. Position Supt. Position Send communications regarding well to Parker Drilling Co. Name
Set & Cemented 115 jts.3592' of 5 Matl.Tube casing Using 200 sks. 0 Plug pumped to 3575' Plug down at drilled 12 A.M. 3-14-41. tested 1 MAR 19 1941 Approved	S AND REGULATIONS OF THE COMMISSION S O.D. 15# Grade H-40 Srd. thrd. new S XI. Tore Cement Halliburton'system 7:30 A.M. 3-11-41 set 72 hrs. Plug hr. baler method. Tested 0.K. Parker Drilling Co. Company or Operator W.E.Snell By

Title	
11010	

•

Houston Texas.