

TIONS

REPORT ON BEGINNING DRILLING OPERA-

## OLL CONSERVATION COMMLICION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days specified is completed. It should be signed and sworn to before a notary public for reports on beginning difficulties are tions, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON REPAIRING WELL

Indicate nature of report by checking below.

REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	.	REPORT ON ALTERI	NG CASING	) I II EIC W ISE	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	Х	REPORT ON	DEEPENING W	ELL	
REPORT ON RESULT OF PLUGGING OF WELL					
July 16, 1 OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO.	947	Date	Mobbs, Me	Place	
Gentlemen: Following is a report on the work done and the resu	ulte ohtai	ned under the hes	ading noted shave	at the	
Cities Service Oil Company			Well No.		
Company or Operator		Lease			
C SN SW of Sec. 3		T. 225	, R37 <u>E</u>	, N.	M. P. M.,
Drinkard Field, Les		T. 3 3 0 3 0 41	<u> </u>		_ County.
The dates of this work were as follows: July 1					
Notice of intention to do the work was (was 100)			=		1947
and approval of the proposed plan was (was not)		•	•		
DETAILED ACCOUNT OF	WORK I	OONE AND RESU	LTS OBTAINED		
Total depth 6570°. Lin J-55 SS casing, 6490° 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli	6500' Ceine	and cemented nt was allowe	with 350 sac ed to set 30	eks. Plug hours, plu	ıg
J-55 SS casing, 6490° 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure applisumed.	\$500° Ceme Led wit	and cemented nt was allowe	with 350 saded to set 30 pressure. I	eks. Plug hours, plu Prilling re	ıg
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli	\$500° Ceme Led wit	and cemented nt was allowe h no drop in	with 350 saded to set 30 pressure. I	eks. Plug hours, plu Crilling re	1g 3-
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli sumed.  Witnessed by R. M. Ely  Name  Subscribed and sworn before me this	S500' Ceine Led wit	and cemented nt was allowed h no drop in Service Cil Compa	with 350 saded to set 30 pressure. I	eks. Plug hours, plu Prilling re istrict Sup	erintenden
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli sumed.  Witnessed by R. N. Ely Name	S500' Ceine Led wit	and cemented nt was allowed h no drop in  Service Ci  Compa  thereby swear or strue and correct  Name	with 350 saded to set 30 pressure. I	eks. Plug hours, plu prilling resistrict Sup	erintenden
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli sumed.  Witnessed by R. Ely Name  Subscribed and sworn before me this 19	S500' Ceine Led wit	and cemented nt was allowed h no drop in  Service Ci Compa hereby swear or strue and correct Name Position District Cepresenting Cit	with 350 saded to set 30 pressure. I	cks. Plug hours, plus prilling resistrict Sur Transformation give tendent	erintenden
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli sumed.  Witnessed by R. Ely  Name  Subscribed and sworn before me this  16th day of July , 19	S500' Ceine Led wit	and cemented nt was allowed h no drop in  Service Ci Compa hereby swear or strue and correct Name Position District Cepresenting Cit	with 350 saded to set 30 pressure. If the set 30 pressure. If the set 30 pressure is service (1 co. Dispersion of the service (1 co.	eks. Plug hours, plu prilling resistrict Sur tinformation give tendent	erintenden
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli sumed.  Witnessed by R. N. Ely  Name  Subscribed and sworn before me this	S500' Ceine Led wit	and cemented nt was allowed h no drop in  Service Ci Compa hereby swear or strue and correct Name Position District Cepresenting Cit	with 350 saded to set 30 pressure. If the set 30 pressure. If the set 30 pressure. If the set 30 pressure is service (Company or Open set 30 pressure is set 30 pressure is set 30 pressure is set 30 pressure. If set 30 pressure is s	eks. Plug hours, plu prilling resistrict Sur Transfer Sur	erintenden
J-55 SS casing, 6490' 2", set at down at 8:30 P. M. July 14, 1947. drilled out, 1000# pressure appli sumed.  Witnessed by R. Ely Name  Subscribed and sworn before me this	S500' Ceine Led wit	and cemented nt was allowed h no drop in  Service Ci Compa hereby swear or strue and correct Name Position District Cepresenting Cit	with 350 saded to set 30 pressure. If the set 30 pressure. If the set 30 pressure. If the set 30 pressure is service (Company or Open set 30 pressure is set 30 pressure is set 30 pressure is set 30 pressure. If set 30 pressure is s	cks. Plug hours, plus prilling resistrict Sur Transformation gives tendent company erator	perintenden itle ven above