


NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature	e or no		
OTICE OF INTENTION TO TEST CASING SHUT-OFF	Х	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
OTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
OTICE OF INTENTION TO DEEPEN WELL			
Houds, W	w Mex	cico January 9, 1950	
		Place Date	
OIL CONSERVATION COMMISSION,			
lanta Fe, New Mexico.			
Gentlemen:		and the below of the	
ollowing is a notice of intention to do certain work. Cities Service Oil Company	rk as de un son		SW
Company or Operator Le	ease		
•	, N	N. M. P. M., Pad dock	_Field.
Lea County.			
FULL DETAILS OF	PROI	POSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE R			
FULLOW INDIRUCTIONS IN THE R	OTES &	AND REGULATIONS OF THE COMMISSION	
			5091
Total depth 5185' lime. Ran 20	61 jts	s. of 5-1/2" OD casing 5079.47' set at	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091.
Total depth 5185' lime. Ran 26 and cemented with 250 sacks. Flug callowed to set 48 hours before test	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of	61 jts down 4	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will for shut-off.	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of allowed to set 48 hours before test	61 jts down 4 ting f	cities Service Oil Company	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of allowed to set 48 hours before test	61 jts down 4 ting f	s. of 5-1/2" OD casing 5079.47' set at ::40 A.M. January 7, 1950. Cement will for shut-off.	5091.
Total depth 5185 lime. Ran 20 and cemented with 250 sacks. Flug of allowed to set 48 hours before test	61 jts down 4 ting f	cities Service Oil Company	5091.
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug callowed to set 48 hours before test	61 jts down 4 ting f	Cities Service Oil Company Company or Operator By	5091. be
Total depth 5185' lime. Ran 20 and cemented with 250 sacks. Flug of allowed to set 48 hours before test	61 jts down 4 ting f	Cities Service Oil Company Company or Operator By Division Superintendent	5091.
Total depth 5185' lime. Ran 26 and cemented with 250 sacks. Flug callowed to set 48 hours before test allowed to set 48 hours before test approved	61 jts down 4 ting f	Cities Service Oil Company Company or Operator By	5091.
Total depth 5185' lime. Ran 26 and cemented with 250 sacks. Flug callowed to set 48 hours before test	61 jts down 4 ting f	Cities Service Oil Company Company or Operator By Position Division Superintendent Send communications regarding well to Name Cities Service Oil Company Company or Operator By Position Division Superintendent Send communications regarding well to	5091.
Total depth 5185' lime. Ran 26 and cemented with 250 sacks. Flug callowed to set 48 hours before test allowed to set 48 hours before test approved	61 jts down 4 ting f	Cities Service Oil Company Company or Operator By Position Division Superintendent Send communications regarding well to	5091. be