


TRIPPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

June 6, 1950

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Cities Service Oil Company **Brunson "C"** Well No. 4 in the

Company or Operator **C NW SE** of Sec. 3, T. 22S, R. 37E, N. M. P. M.,
Drinkard Field, Lea County.

The dates of this work were as follows: April 1, 2 & 3, 1950

Notice of intention to do the work was (~~was~~/~~not~~) submitted on Form C-102 on March 31 19 50
and approval of the proposed plan was (~~was~~/~~not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to a T.D. of 6561' and completed as a Drinkard pay well with 5½" casing set at 6475' and cemented with 350 sax. In order to avoid possible water encroachment from behind the casing in this well to the Paddock Zone the casing was perforated and squeezed as follows: Set plug at 5225', covered with 4' Calseal and perforated from 5210' to 5214' with 4 shots and squeezed with 193 sax in 2 stages. Perforated 5070' to 5074' with 4 shots and squeezed with 90 sax., perforated 5120' to 5130' with 21 shots (in Paddock Pay) well tested dry. Set retainer at 5089' and squeezed with 85 sax. Drilled retainer and put well on production.

Witnessed by R. W. Ely **Cities Service Oil Company** Dist. Supt.
Name Company Title

Subscribed and sworn before me this
6 th day of June 1950

Fred Lawson

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]

Position District Superintendent

Representing Cities Service Oil Company
Company or Operator

My commission expires February 8, 1954

Address Drawer G., Hobbs, New Mexico

Remarks:

APPROVED

[Signature]
Name
Title