
## NEW MEXICO OIL CONSERVATION COMMISSION

## SANTA FE, NEW MEXICO



hegin. A copy vil	in triplicate to the be returned to the	Oil Conservation ( le sender on whic	Commission or its protect will be given the a of the plan submitte	oper agent before the pproval, with any mo	e work specified difications cons
ed, and work shou	bjection by the Com ld not begin until a	nmission or agent, pproval is obtaine	, <b>of the plan submitte</b> ed See additional ins	d. The plan as approtructions in the Rule	oved should be t es and Regulati
the Commission.	In	ndicate nature of	notice by checking b	elow:	
NOTICE OF INTI- SHUT-OFF	ENTION TO TEST	CASING		TENTION TO SHOOLLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS			NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING		
NOTICE OF INTENTION TO REPAIR WELL			NOTICE OF INTENTION TO PLUG WELL		
NOTICE OF INTE	ENTION TO DEEPE	EN WELL			
	Hobbs,	New Mexico	J	Tune 16, 1947	· · · · · · · · · · · · · · · · · · ·
			Place		Date
OIL CONSERVAT	TION COMMISSION	Ι,			
Santa Fe, New M		',			
Gentlemen:	-				
	ion of into-tion to i	la contair monle -	a decembed below a	t tha	
	of intention to o		s described below a	•	C N
Company or O		Lease		Well No	
of Sec. 3	T 22S	P 37E	_, N. M. P. M.,	Drinkard	
	, 1		IV. IVI. I'. IVI.,		
OI Dec.					
Les	_ <del>-</del>		ROPOSED PLAN ES AND REGULATI		MISSION
FOLLO	W INSTRUCTIONS	ETAILS OF P	ES AND REGULATI	ONS OF THE COMP or 2800° of 8 5	5/8*
FOLLO	W INSTRUCTIONS  Total depth	ETAILS OF P S IN THE RULI 2810' lime.	ES AND REGULATI  Ran 65 joints  O' and comented	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF P S IN THE RULI 2810' lime. ag set at 281 6/16/47. Ce	Ran 65 joints of smd cemented ment will be al	ONS OF THE COMP Or 2800° of 8 5 with 500 sacks	5/8# !•
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin  n at 6:30 AM,  fore testing f	ETAILS OF PS IN THE RULI 2810 lime.  2816 11me.  2816/47. Ce cor shut off.	ES AND REGULATI  Ran 65 joints of smd cemented ment will be al	ONS OF THE COMMOR 2800° of 8 5 with 500 sacks	6/8* •
FOLLO OD, 28#, Plug dow hours be	W INSTRUCTIONS  Total depth  BR thd. Casin n at 6:30 AM,	ETAILS OF PS IN THE RULI 2810 lime.  2816 11me.  2816/47. Ce cor shut off.	ES AND REGULATI  Ran 65 joints of smd cemented ment will be al	or 2800° of 8 5 with 500 sacks lowed to set 50	i/8*
FOLLO OD, 28#, Plug dow hours be	W INSTRUCTIONS  Total depth  BR thd. Casin  n at 6:30 AM,  fore testing f	ETAILS OF PS IN THE RULI 2810 lime.  2816 11me.  2816/47. Ce cor shut off.	ES AND REGULATI  Ran 65 joints of smd cemented ment will be al	ONS OF THE COMMOR 2800° of 8 5 with 500 sacks	i/8*
FOLLO OD, 28#, Plug dow hours be	W INSTRUCTIONS  Total depth  BR thd. Casin  n at 6:30 AM,  fore testing f	ETAILS OF PS IN THE RULI 2810 lime.  2816 11me.  2816/47. Ce cor shut off.	ES AND REGULATI  Ran 65 joints of smd cemented ment will be al	or 2800° of 8 5 with 500 sacks lowed to set 50	i/8*
FOLLO OD, 28#, Plug dow hours be	W INSTRUCTIONS  Total depth  BR thd. Casin  n at 6:30 AM,  fore testing f	ETAILS OF PS IN THE RULI 2810 lime.  2816 11me.  2816/47. Ce cor shut off.	Ran 65 joints O' and comented ment will be al	or 2800° of 8 5 with 500 sacks lowed to set 50	any
FOLLO OD, 28#, Plug dow	W INSTRUCTIONS  Total depth  BR thd. Casin  n at 6:30 AM,  fore testing f	ETAILS OF PS IN THE RULI 2810 lime.  2816 11me.  2816/47. Ce cor shut off.	Cities Se	or 2800° of 8 5 with 500 sacks lowed to set 50  crvice Oil Comps	any tor endent ding well to