

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	9-5/8"	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

March 1, 1949

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Gulf Oil Corporation Mark \_\_\_\_\_ Well No. 7 in the \_\_\_\_\_

Company or Operator SE NE of Sec. 3, T. 22S, R. 37E, N. M. P. M.,  
Drinkard Field, Lea County.

The dates of this work were as follows: Cemented on Feb. 26, 1949. Tested on Feb. 28, 1949.

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on February 28, 1949  
 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

After waiting forty-eight hours, the casing was tested with 1200# pressure applied for 30 minutes. The plug was drilled and the casing and cement were tested with 1200# pressure applied for 30 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil & Gas Inspector, preparations were made to drill ahead.

Top of cement back of 9-5/8" csg @ 1260' per temperature survey.

Witnessed by Glenn Stach Gulf Oil Corporation Drilling Foreman  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

1st day of March 19 49

Name E. J. Gallagher

Position District Sup't.

[Signature]  
Notary Public

Representing Gulf Oil Corporation

Company or Operator

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks:

[Signature]  
Name  
Title

## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	9-5/8"	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

February 28, 1949

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Gulf Oil Corporation Mark Well No. 7 in SE NE  
Company or Operator Lease  
of Sec. 3, T. 22S, R. 37E, N. M. P. M., Drinkard Field.  
Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

On February 26, 1949, ran 89 jts of new 9-5/8" OD, 36#, 8 Rd Thd, H-40, R-2, SS csg w/short T&C. Tallies 2787', H-13', set @ 2800'. Cemented by Halliburton w/1200 sacks of 2% HOWCO Jel and 100 sacks of common Portland bulk cement. Plug @ 2764'. Job started @ 9:40 a.m. and completed @ 3:30 p.m.

Propose to drill plug and test shut-off @ 3:30 p.m., February 28, 1949.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Gulf Oil Corporation

Company or Operator

By Chas. F. TaylorPosition General Foreman

Send communications regarding well to

Name Chas. F. TaylorAddress Box 1667, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Ray Yankraugh

Title \_\_\_\_\_