

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

5a. Indicate Type of Lease
State ☐ Fed ☒
5. State Oil & Gas Lease No.

SUNDARY NOTICES AND REPORTS ON WELLS

100. NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPERF OR PLUG WELLS TO A DIFFERENT RESERVOIR.
USE FORM C-101 FOR SUCH PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
Amoco Production Company
3. Address of Operator
P. O. Box 68, Hobbs, New Mexico 88240
4. Location of Well
UNIT LETTER E 1980 FEET FROM THE North 660
THE West LINE, SECTION 3 TOWNSHIP 22-S RANGE 37-E
15. Elevation (Show whether DF, RT, CR, etc.)
3433' DF
12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Process or Complete Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to treat the subject well for paraffin and place on pump if necessary as follows:
Rig up swab unit and swab to evaluate. If acidizing is necessary, then proceed as follows:

- Acidize with 1050 gals A-Sol, 1950 gals. of 15% HCL, 2 gals/1000 iron sequestering agent, and 1 gal/1000 corrosion inhibitor. Pump at 3-5 BPM.
- Flush acid to perfs with 1185 gals of 2% KCL. Swab to evaluate. If necessary install pumping equipment as follows:

- RIH with 2-3/8" SN and 5 jts 2-3/8" J-55 tubing and 2-3/8" x 5" tubing anchor-catcher x 6340 ft 2-3/8" J-55 tubing
- Set anchor at 6340 ft. Set pump at 6490 ft.
- RIH with 2 x 1-1/4" x 14' RHBC pump with 6' plunger 4400' 3/4" grade D rods, with full size couplings (176 rods). 2080' 7/8" Grade D rods with SH couplings (83 rods & ponies)
- Set a 114 pumping unit in its longest stroke length with a 10 HP motor. The unit must have at least 15,000# beam rating.
- Sheave the unit to run at 8.4 SPM for 54" stroke and 10.1 SPM for 48" stroke.
- Balance the unit. This should require appx. 12,730# effective counterbalance.
- Put well on production.

0+4-NMOC.D.H. 1-HOU R. E. Ogden RM 21.150 1-F. J. Nash, HOU RM 4.206 1-SUSP

1-PJS 1-Peter Lewis

Putu J. Serna

TITLE Assist. Admin. Analyst

DATE 10-5-83

ORIGINAL SIGNED BY

JERRY SEXTON

OCT 11 1983

TITLE

DATE

DISTRICT SUPR.