

**ATTACHMENT TO FORM C-105
COLLINS & WARE, INC.
CORRIGAN, H #4**

26. Perforation Record.

Drinkard	6518 - 6566 (144 shots)	12/46
Tubb	6125 - 6295 (580 shots)	5/54
Drinkard	6357 - 6458 (40 holes)	4/75
Tubb	6028 - 6093 (16 holes)	4/75
Blinebry	5527 - 5922 (90 holes)	11/96

27. Treatment Record.

6518 - 6566	AT w/2000 gals Western 15% acid.
6573	Pushed junk to 6573'. 5/54
6240 - 6295	AT w/500 gals Western 15% acid. 5/54
6125 - 6215	AT w/500 gals Western 15% acid.
6125 - 6295	FT w/5000 gals and 2500# sand.
6518 - 6566	FT w/5000 gals Western gel and 2500# sand. 5/54
6500	Set CIBP with 2 sacks cement on top. 3/75
6357 - 6458	AT with 2800 gals 15% NE LST
6357 - 6458	FT w/30,000 gals and 42,000# 20/40 sand. 4/75
6028 - 6093	AT w/3210 gals 20% retarded acid.
6110	Set BP at 6110 with 1 sack sand on top.
6028 - 6093	Squeeze perfs with 250 sx cement
6125 - 6295	Had communication on squeeze job and squeezed lower Tubb perfs also.
6020	Set CIBP at 6020' and dumped 35' of cement on top. 11/96
5527 - 5922	AT w/4000 gals 15% Ferchek SC.
5527 - 5922	FT w/75,000 gals Delta Frac 26 with 200,000# 16/30 Ottawa sand. 11/96