NEW A ICO OIL CONSERVATION COMM YON

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

of the Commission.				
REPORT ON BEGINNING	DRILLING OPERATIONS	REPORT ON	REPAIRING WELL	
REPORT ON RESULT OF S TREATMENT OF WELL	SHOOTING OR CHEMICAL	REPORT ON ALTERIN	PULLING OR OTHERW	ISE
REPORT ON RESULT OF SHUT-OFF	TEST OF CASING	x REPORT ON	DEEPENING WELL	_
REPORT ON RESULT OF I	PLUGGING OF WELL			
	Monument, N	ew Mexico	June 9	1937
OIL CONSERVATION CO	OMMISSION,	Place	Dat	re
Santa Fe, New Mexico.				
Gentlemen:				
Following is a report on	the work done and the res			_
Amerada Petroleus		Corris Lease	Well No.	in the
1	or Operator of Sec. 4		R. 37	, N. M. P. M.,
Penrose	Field,	_		County
The dates of this work w				
nd approval of the prop DETAIL 8-5/8" 32# 8-Thd	osed plan was [was not] of ED ACCOUNT OF W New Seamless cas Method with 400 sac	obtained. (Cross out incomposed on the control of t	rrect words.) RESULTS OBTAIN	
nd approval of the prop DETAIL 8-5/8" 32# 8-Thd. the Halliburton b Casing and fitting undisturbed for to drilled out of the and allowed to st	ED ACCOUNT OF W. New Seamless case Method with 400 sach mass were tested with thirty minutes. No me casing and the stand undisturbed for	obtained. (Cross out income VORK DONE AND Holding was set in this ks. h 1200# pump pressure is drop in pressure is sme test of 1200# j	RESULTS OBTAIN B well at 1238' a ure and allowed resulted so the opump pressure was	and cementedby to stand cement was then s again applies
DETAIL 8-5/8" 32# 8-Thd. the Halliburton because and fitting undisturbed for the drilled out of the and allowed to state the drilling was	. New Seamless cas Method with 400 sachings were tested with thirty minutes. No me casing and the stand undisturbed for then resumed.	obtained. (Cross out income VORK DONE AND Holding was set in this ks. h 1200# pump pressure is drop in pressure is sme test of 1200# j	RESULTS OBTAIN s well at 1238 a ure and allowed resulted so the opump pressure was No drop in press	and cementedby to stand cement was then s again applies
DETAIL 8-5/8" 32# 8-Thd. the Halliburton because and fitting undisturbed for the drilled out of the and allowed to state drilling was	. New Seamless cas dethod with 400 sach mass were tested with thirty minutes. None casing and the stand undisturbed for then resumed. Stewart Name	obtained. (Cross out incomposed of the control of t	RESULTS OBTAIN B well at 1238 a ure and allowed resulted so the opump pressure was No drop in press Co.	and cemented by to stand cement was then s egain applied sure resulted
DETAIL 8-5/8" 32# 8-Thd. the Halliburton becasing and fitting undisturbed for the drilled out of the and allowed to state drilling was Vitnessed by L.E.	. New Seamless cas dethod with 400 sach mass were tested with thirty minutes. None casing and the stand undisturbed for then resumed. Stewart Name	obtained. (Cross out incomposed of the control of t	RESULTS OBTAIN B well at 1238 a ure and allowed resulted so the opump pressure was No drop in press Co.	and cementedby to stand cement was then s egain applies are resulted
DETAIL 8-5/8" 32# 8-Thd. the Halliburton M Casing and fitting undisturbed for the drilled out of the and allowed to state drilling was Witnessed by L.E.	New Seamless cas Method with 400 sac mags were tested with thirty minutes. No me casing and the stand undisturbed for then resumed. Stewart Name	obtained. (Cross out incomposed of the control of t	RESULTS OBTAIN B well at 1238 a ure and allowed resulted so the opump pressure was No drop in press Co.	and cemented by to stand cement was then s egain applied sure resulted
DETAIL 8-5/8" 32# 8-Thd. the Halliburton Management of the drilled out of the and allowed to state drilling was Witnessed by L.E.	. New Seamless cas dethod with 400 sach mass were tested with thirty minutes. None casing and the stand undisturbed for then resumed. Stewart Name	ing was set in this ks. h 1200# pump pressume drop in pressume sme test of 1200# r thirty minutes. Noble Drilling Company I hereby swear of is true and correct Name	RESULTS OBTAIN B well at 1238' ure and allowed resulted so the pump pressure was No drop in press cr affirm that the inforct. Forman Amerada Petrols Company or	to stand cement was there is again applied sure resulted companies the stand cement was there are resulted companies the stand
DETAIL 8-5/8" 32# 8-Thd. the Halliburton Marilled out of the and allowed to state the drilling was Witnessed by L.E.	New Seamless cassisthed with 400 sacings were tested with thirty minutes. None casing and the stand undisturbed for then resumed. Stewart Name Notary Public	ing was set in this ks. h 1200# pump pressure drop in pressure sme test of 1200# r thirty minutes. Noble Drilling Company I hereby swear of is true and correct Name Position	RESULTS OBTAIN B well at 1238' ure and allowed resulted so the pump pressure was No drop in press cr affirm that the inforct. Formen Amerada Petrole	to stand cement was there is again applied sure resulted companies the stand cement was there are resulted companies the stand
DETAIL 8-5/8" 32# 8-Thd. the Halliburton Is Casing and fitting undisturbed for the drilled out of the and allowed to state drilling was Witnessed by L.E. Subscribed and sworn day of	New Seamless cassisthed with 400 sacings were tested with thirty minutes. None casing and the stand undisturbed for then resumed. Stewart Name Notary Public	ing was set in this ks. h 1200# pump press drop in pressure sme test of 1200# r thirty minutes. Noble Drilling Company I hereby swear of is true and correct Name Position Representing	RESULTS OBTAIN B well at 1238' ure and allowed resulted so the pump pressure was No drop in press cr affirm that the inforct. Forman Amerada Petrols Company or	to stand cement was there is again applied sure resulted companies the stand cement was there are resulted companies the stand

Title