

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico

December 15th., 1937

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

**DUPLICATE**

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Amerada Petroleum Corporation H. Corrigan Well No. 2 in the \_\_\_\_\_  
 Company or Operator Lease  
SE 4 NE 4 of Sec. 4, T. 22, R. 37, N. M. P. M.,  
Penrose Field, Lea County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was [~~request~~] submitted on Form C-102 on December 13th., 1937  
 and approval of the proposed plan was [was not] obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

**6-5/8"-20#, 10thd., New seamless was set in this well at 3587' and cemented with 500 sacks cement by the Halliburton method.**

The cement was allowed to stand undisturbed for 72 hours. The casing and connections were then tested with 1200# pump pressure and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted so the cement was then drilled out of the casing and the same test of 1200# pump pressure was again applied and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted so the drilling was then resumed.

Witnessed by Bill Hines Two States Drilling Co., Tool-Pusher & Partner  
 Name Company Title

Subscribed and sworn to before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

17 day of December, 1937

Name J. E. Low

Lewis B. Warrick

Position Supt.,

Notary Public

Representing Amerada Petroleum Corp.,

My Commission expires Dec. 21, 1940

Address Monument, New Mexico,

Remarks:

Guy Shepard  
 Name  
 \_\_\_\_\_  
 Title