


DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS OF WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Perforating & Squeezing	X

Monument, New Mexico

Place

October 31, 1946

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation H. Corrigan Well No. 5 in the
Company or Operator Lease

SW 1/4 of NE 1/4 of Sec. 4, T. 22S, R. 37E, N. M. P. M.,
Brunson Field, Lea County.

The dates of this work were as follows: October 28 and 29, 1946

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19____
and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7813' Total Depth, Perforated with 3 holes at 7770' and set Model K Baker cement Retainer at 7759' and squeezed with 15 sacks common cement, Perforated with 3 holes at 7675' and set Baker Model K Cement Retainer at 7662' and squeezed with 40 sacks common cement and built up 3000# Pressure, Perforated with 3 holes at 7560' and set Baker Model K Cement Retainer at 7545' and squeezed with 40 Sacks common cement and built up 3400#. pulled tubing out of hole and will let cement set 24 hours.

Witnessed by K. V. Stephenson Amerada Pet. Corp. Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

31 day of October, 1946Name BowditchPosition Asst. Dist. Supt.Representing Amerada Pet. Corp.
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date NOV 1 1946

Roy Markrough
Name
Oil & Gas Inspector
Title