


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



HOBBS OFFICE

DUPLICATE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

Monument, New Mexico.

Place

September 6, 1946

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation H. Corrigan Well No. 5 in the
Company or Operator Lease

SW $\frac{1}{4}$ of NE $\frac{1}{4}$ of Sec. 4, T. 22S, R. 37E, N. M. P. M.,
Brunson Field, Lea County.

The dates of this work were as follows: September 5, 1946

Notice of intention to do the work was ~~(insert)~~ submitted on Form C-102 on September 5, 1946
and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2775' Total Depth Line, Ran 68 Joints of 8 5/8" OD 32#, J-55, R-3, 8 Round Thread Spang Seamless Steel Casing and set at 2766' and cemented with 1000 Sacks 2% Howcogel Common Cement and 50 Sacks Incor Cement and plug pumped to 2724' at 3:30PM September 5, 1946. On September 6, 1946 ran temperature Survey and found top of cement at 1225' outside of 8 5/8" Casing, 34% of calculated fill.

Witnessed by Don Topper Name Amerada Pet. Corp., Asst. Dist. Supt.
Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

6 day of September, 1946

Name Don Topper

Position Asst. Dist. Supt.

Representing Amerada Pet. Corp.,
Company or Operator

My commission expires My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date SEP 9 1946

Roy. Yarbrough
Name
Oil & Gas Inspector
Title