

**ATTACHMENT TO FORM C-105
COLLINS & WARE, INC.
CORRIGAN #8**

26. Perforation Record.

6524 - 6571	(188 shots) 3/47	Drinkard
6340 - 6502	(1 SPF, 24 shots) 7 /73	Drinkard
5660 - 5744	(1 JSPF, 30 holes) 11/97	Blinebry

27. Treatment Record.

6524 - 6571	AT with 1000 gals Western 20% Low Tension Acid. 3/47
6524 - 6571	Sand oil Frac with 20,000 gals Famariss 24 gravity refined oil and 20,000# sand. 4/55
6524 - 6571	AT with 2300 gals 15% NE acid. 7/73
6340 - 6502	AT with 3100 gals 15% NE acid. 7/73
6340 - 6502	FT with 31,000# 20/40 sand and 28,560 oil base ultra-frac with 400# moth balls. 7/73
6300	Set CIBP at 6300'. 11/97
5725 - 5744	AT with 1760 gals 15% Ferchek acid and 30 ball sealers. Achieved ballout.
5660 - 5669	AT with 950 gals 15% Ferchek acid and 15 ball sealers. Achieved ballout.
5660 - 5744	FT with 55,000 gals Delta Frac and 175,730# sand. 11/97