

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES 1962 JUN 4 AM 7:25

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	X-Dual Completion

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Eunice, New Mexico
(Place)

May 31, 1962
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation - H. Corrigan Well No. 9 in Q
(Company or Operator) (Unit)
SW/NE/ 1/4 of Sec. 4, T. 22, R. 37-E, NMPM, Drinkard Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

6570' TD - 5567' DOD - Pull tubing, run gamma ray neutron logs from zero to 6567', Detail logs from 3900' to 6567'. Run 3 1/2" OD EUE Tubing w/packer & set @ 6530'. Sand-oil fracture perforations 6530' to 6565' w/20,000 gallons of lease crude oil and 20,000 lbs. 20-40 sand w/ball sealers and fluid loss control additives, treat with 1000 gallons of 15% regular acid in stages while fracturing, swab test. Pull 3 1/2" tubing and perforate Blinebry oil zone with 2 shots per foot selectively from logs from approximately 5790' to 5920'. Run retrievable bridge plug and packer on 3 1/2" tubing, set bridge plug at approximately 5950', sand-oil fracture perforations from 5790' to 5920' with 30,000 gallons lease crude oil and 60,000 lbs. 20-40 sand with fluid loss additives, treat with 1000 gallons of 15% regular acid in stages while fracturing, swab test. If both zones are commercial, run Model "D" Packer 2 strings of 2-1/16" tubing & complete as a dual oil well.

Approved....., 19.....
Except as follows:

Amerada Petroleum Corporation
Company or Operator
By B. A. Moe
Position Asst. Dist. Supt.

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Send Communications regarding well to:

Name Amerada Petroleum Corporation
Address Box 706, Eunice, New Mexico