

**ATTACHMENT TO FORM C-105  
COLLINS & WARE, INC.  
CORRIGAN, H. #10**

**26. Perforation Record**

6538 - 6570	(128 shots)	4/47	Drinkard
6338 - 6477	2 SPF (50 holes)	3/75	Drinkard
5041 - 5058	1 SPF	6/97	Paddock
5180 - 5260	1 SPF	6/97	Paddock

**27. Treatment Record**

6538 - 6570	AT with 3000 gals Western 20% Low tension acid.	4/47
6538 - 6570	AT with 2000 gals 15% NE acid.	8/73
6538 - 6570	AT with 1000 gals Dowell XF-63 acid.	6/74
6520'	Set BP at 6520' with 5' of sand on top. Top of sand at 6515'.	3/75
6338 - 6477	AT with 3000 gals 15% NEA.	3/75
6338 - 6477	FT with 40,000 gals Ultra-Frac 15, 46,500# 20/40 sand.	3/75
6300	Set CIBP at 6300' and dump 4 sx cement on top.	6/97
5041 - 5058	AT with 2000 gals 15% HCL acid.	6/97
5240 - 5260	AT with 15% Ferchek SC acid.	6/97
5180 - 5200	AT with 1000 gals 15% Ferchek SC acid.	6/97
5041 - 5260	FT with 35,000 gals Delta Frac 25 carrying 1000 sx 20/40 Ottawa sand.	6/97

Well was spud March 6, 1947

*Handwritten signature/initials*