


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

April 17, 1947

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation H. Corrigan Well No. 10 in the _____
Company or Operator Lease

SE 1/4 NE 1/4 of Sec. 4, T. 22S, R. 37E, N. M. P. M.,
Drinkard Field, Lee County.

The dates of this work were as follows: April 16, 1947

Notice of intention to do the work was ~~(insert)~~ submitted on Form C-102 on April 14, 1947 19____
and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6574' Total Depth Line, Ran Temperature Survey and found top of cement at 4391', 86.3% of Calculated fill, Picked up tubing and found top of cement at 6530' tested casing with 1200# for 30 minutes and was OK, drilled out cement to 6573' and tested casing with 1200# for 30 minutes and was OK, Gun Perforated with Lane wells from 6538' to 6570' and ran 210 fts 2" BUE 4.7#, J-55, R2-, 8 RT Spang seamless Steel Tubing and set at 6569' with 1-3' Perforated Nipple on bottom bull plugged and displaced mud with 130 barrels oil and will acidize with 3000 gallons of Acid.

Witnessed by K. V. Stephenson Amerada Pet. Corp. Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

17 day of April, 19 47Name Don TupperPosition Asst. Dist. Supt.Representing Amerada Pet. Corp.
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

APR 18 1947

Roy. Yarbrough
Name
Oil & Gas Inspector
Title