

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

## MISCELLANEOUS NOTICES

1954 APR 7 PM 1:11

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOEunice, New Mexico  
(Place)April 6, 1954  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Amerada Petroleum Corporation,** **H. Corrigan** Well No. **11** in **A**  
(Company or Operator) (Unit)

**NE/**  $\frac{1}{4}$  **NE/**  $\frac{1}{4}$  of Sec. **4**, T. **22-S**, R. **37-E**, NMPM, **Brunson** Pool  
(40-acre Subdivision)

**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Load hole with oil emulsion mud and lost circulation material, pull tubing, drill out cement and bridge plugs from 7453' to 7460' and 7517' to 7520' and clean out to old D.O.D. of 7580', leaving open perforations from 7410' to 7445', 7466' to 7510' and 7538' to 7570', acid-frac these three sections together using 1,000 gallons M38 acid followed by 4,000 gallons Jel X-410 and 4,000# sand followed by 2,000 gallons M-38 Acid. Then run H.R.C. Retainer and test casing, perforate casing at approximately 5555' to 5645' in the Blinbry Zone, Acidize with 500 gallons and test. If this Section does not produce gas, perforate from 5680' to 5765' in the Blinbry Zone, acidize with 500 gallons and test. Then Dual complete to produce gas from the Blinbry Zone through casing and oil from the Brunson Zone through Tubing.

Approved....., 19.....  
Except as follows:

**Amerada Petroleum Corporation**  
Company or Operator

By.....

Position **Foreman**

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name. **Amerada Petroleum Corporation**

Title.....

Address. **Box 706, Eunice, New Mexico**