

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
NOV 28 1947
HOODS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 25, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation H. Corrigan Well No. 11 in the
Company or Operator Lease
NE¹/₄ NE¹/₄ of Sec. 4, T. 22S, R. 37E, N. M. P. M.,
Brunson Field, Lea County.

The dates of this work were as follows: November 22 to 25, 1947

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on November 21, 1947
and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7600' Total Depth, Granite. 7580' Drilled Out Bepth. Ran temperature survey and found top of cement at 3475'. Drilled out cement from 7515' to 7580' and tested casing with 1000# for 30 minutes before and after drilling cement and was OK. Perforated W/Lane Wells from 7538' to 7570', 128 holes. Ran Wilson Hook Wall Packer and 243 jts. of 2" EUE, 4.7#, J-55, R-2, 8-RT 88 Tubing W/Packer set at 7473' and tbg. set at 7569' W/1-3' perf. sub on bottom bull plugged and 1-4' sub on Packer. Displaced mud with 180 bbls. of oil and started swabbing. In 13 hrs. to 6:00AM, 11-25-47 had swabbed 30 bbl. oil to tanks. Made two heads of gas for about 15 minutes each, the first with spray of oil, the second without oil.

Witnessed by <u>D. W. Gordon</u>	<u>Amerada Petroleum Corporation</u>	<u>Farm Boss</u>
Name	Company	Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

25th. day of November, 1947

Name Ken Taylor

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED
NOV 28 1947

Date _____

Roy Yarbrough
Name
OIL & GAS INSPECTOR
Title