

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
NOV 26 1947
RECEIVED
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

November 21, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation **H. Corrigan** Well No. **11** in the _____
Company or Operator Lease
NE $\frac{1}{4}$ NE $\frac{1}{4}$ of Sec. **4**, T. **22S**, R. **37E**, N. M. P. M.,
Brunson Field, **Lea** County.

The dates of this work were as follows: **November 21, 1947**

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **November 21,** 19 **47**
and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7600' Total Depth, Granite. Ran Schlumberger Survey. Ran total of 193 joints of 5-1/2"OD, 15.5# & 17#, J-55, R-3, 8-RT, SS Casing New with one second hand joint with 50 jts. of 17# on bottom, 81 jts. of 15.5# in middle and 62 jts. of 17# on top and casing set at 7600'. Nine Larkin Centralizers set at: 7345', 7375', 7405', 7435', 7465', 7495', 7525', 7555', 7585'. Spot welded first five collars. Cemented with 600 sacks of Missouri Reg. Bulk Cement and 50 sacks of Incor Cement and plug pumped to 7515' at 10:50PM, 11-21-47. Final pressure 1800#.

Witnessed by **D. W. Gordon** **Amerada Petroleum Corporation** **Farm Boss.**
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

21st. day of **November**, 19 **47**

Name **L. W. Tapp**

Position **Asst. Dist. Supt.**

Representing **Amerada Petroleum Corporation**
Company or Operator

My commission expires **By Commission Expires May 9, 1948**

Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED
NOV 26 1947
Date _____

Rog. Yarbrough
Name
OIL & GAS INSPECTOR
Title