

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK & <b>Recomplete</b> <b>X</b>		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)October 14, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Gulf Oil Corporation** **W. M. Rinehart** Well No. **2** in **E**  
(Company or Operator) (Unit)  
**SW**  $\frac{1}{4}$  **NW**  $\frac{1}{4}$  of Sec. **4**, T. **22-S**, R. **37-E**, NMPM., **Wantz Abo** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

PBD 7558'. Wantz Abo perfs 7132-7245'. Well presently Temporarily Abandoned.

It is proposed to plug back and recomplete in Penrose Skelly Pool as follows:

1. Set CI bridge plug above Abo perfs at approx. 7050'. Dump 2 sx cement on BP. Set CI bridge plug at approx. 3900' and dump 2 sx cement on top.
2. Run Howco's Hydrajet on 2-3/8" OD tbg with hydraulic holddown. Run GR tie-in log for depth control. Perforate at 3734', 3722', 3694' and 3674'.
3. Treat with four 4,000 gallon stages of refined oil containing 1/40# Adomite M-II and 3# SPG.
4. Swab and test.

Approved....., 19.....  
Except as follows:Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Gulf Oil Corporation  
Company or Operator

By.....

Position.....  
Send Communications regarding well to:

Name.....

Address.....