

Orig: ~~AS~~ ~~SCS~~
cc: ~~DAW~~
File

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED

SEP 6 - 1950

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	<input checked="" type="checkbox"/>	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

~~August~~ Sept. 1, 1950 Hobbs, New Mexico
Date Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Sinclair Oil & Gas Co. R. L. Brunson Well No. 7 in the _____

Company or Operator Lease

of Sec. 4, T. 22, R. 37, N. M. P. M.,

Drinkard Field, Lea County.

The dates of this work were as follows: August 10, 1950

Notice of intention to do the work was (was not) submitted on Form C-102 on August 9, 19 50

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran Gamma Ray Electric log - Set Halliburton retainer and set @ 6517 and cemented off old perforations w/100 sacks of cement - McCullough Jet gun perforated w/20 shots from 6511 to 6516 - Set Baker retrievable retainer @ 6500 and acidized w/500 Gallons of 15% regular acid. - Pulled tubing and removed Baker retrievable retainer and placed well on pump. Pumped 2 Bbl. Oil - 28 Bbl. water - Pulled rods & tubing - Squashed off perforations 6510 to 6516 - Perforated 6488 to 6500 - Acidized w/1000 Gal. Reg. acid Swabbed back load. - Well flowing 24 Barrels of oil per 24 Hrs. - GOR 2500 - Csg. Press 610#

Witnessed by The WESTERN CO. Glenn Holloway Engineer
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

1st day of Sept. 19 50

Name W. B. Brunson

Position Dist. Supt.

Representing Sinclair Oil & Gas Co.
Company or Operator

My commission expires 2-4-54

Address Box 1427 Hobbs, N.M.

Remarks:

Please set Sept. allowable @ 24 barrels per day

W. B. Brunson
Name
Oil & Gas Inspector
Title

APPROVED
SEP 6 - 1950
Date

181
182

Handwritten signature or scribble

Handwritten mark or signature