FORM C-101

NEW MEXIC OIL CONSERVATION COMMISSIC

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

			Hobbs, N.M.	5-3-37
CONSER	VATION	N COMMIS	SION, Place	Inte
tlemen:	Sa: hereby	nta Fe, Ne notified th:	w Mexico It it is our intention to commence the drillin	ng of a well to be known as $\frac{1}{NW/4}$
<u>ell Pe</u>	trol	eum Co:	poration w. R. Minster Company or Operator Lease Penrose N. M. P. M.	Well Noin Field,County.
	N.		The well is 2310 feet [4.] [S.] o	of the North line and 2310 feet
			[E.] [X.] of the West line of	Section 4 ubdivision lines. Crossoutwrong directions.)
			If state land the oil and gas lease is No	
			If patented land the owner is	
			If government land the permittee is	Int. Hr.
			Address The lessee is Shell Petroleum	Corporation
AR	EA 640 4	ACRES CORRECTLY	Address Houston, Texas	quipment as follows: Steam rotary

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:\_\_\_\_

Address Dr. #1457 - Hobbs, N.M.

We propose to use the following strings of casing and to land or cement them as indicated:  $\frac{1}{2}$ 

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Coment
12: 8:2	9 5/8 7	36 24	New "	1200' 3600'	002. C02.	700 sax 150 sax
-					<u></u>	-

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate

that the first productive oil or gas sand should occur at a depth of about 3650 \_\_\_\_feet.

Additional information: A single joint of 122" conductor pipe will be set immediately n the top of the hole. The first cemented string will be landed on top of the alt & cemented to the surface. In the event that ciruclation of cement is not btained initially, the top of the cement behind the casing will be determined, asing perforated at that point, and recemented until the surface is reached.

Approved193719	Sincerely yours,
except as follows:	Shell Petroleum Corporation
	B. Achuence
	Position District Engineer
THE TYON COMMENDA	Send communication regarding well to
OIL CONSERVATION COMMISSION,	Name Shell Petroleum Corporation

OIL CONSERVATION	
By Juny A	hipard
Title	- to the second