013	TRIBUTION	
SANTA FE		1
FILC		
U.S.G. 5		1
LAND OFFICE		1
TRANSPORTER	OIL	1
	GAS	1 i
PRORATION OFFIC	E	
OPERATOR		

4-0CC

## NEW MEXICO OIL CONSERVATION COMMISSION 1-File

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which while given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER		
Notice of Intention to Plug Well	Notice of Intention to Plug Back	X	Notice of Intention to Set Liner		
Notice of Intention to Squeeze	Notice of Intention to Acidize		Notice of Intention to Shoot (Nitro)		
Notic <b>e of Intention</b> to Gun <b>Perforate</b>	Notice of Intention (Other)		Notice of Intention (Other)		

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs, New Mexico

.....

January 15, 1965

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

	Tidews	ater 0il (	Company		R		<u>Clift</u>			Well No	2	in	M	
		(Company or O	perator)			 	Less						(Unit)	
SW 1/40-acre	SW Subdivision)	<sup>1</sup> /4 of Sec	4	, T'	22	\$ R	37	<b>B</b>	.,ħ7 <b>MPM.,</b>		Drinkard			Peol

Lea.....County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Well #2 is completed in the Drinkard zone thru perf. 6520-80 and currently pumps 2 BOPD. It is proposed to plug off the Drinkard and recomplete in the Blinebry as follows: Run Gamma Ray-Neutron log. Set cast iron bridge plug at 6500', dump two sacks cement on top. Pick Blinebry perforations and perforate approximately 5772-5900'. Ran 3" tubing with treating packer and treat perfs. with 1000 gals. acid using ball sealers. Fracture with 30,000 gals. lease oil and 30,000# sand. Pull 3" tubing and packer. Run 2" and retrievable packer. Swab to flowing.

Approved, 19	Tidewater Oil Company
Except as follows:	Original Signed By
	ByC. L. WALL
	Position. Area Supt.
Approved OIL CONSERVATION COMMISSION	Send Communications regarding well to:
By	Name
Title	Address