

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

RECEIVED

MAR 7 1951

OIL CONSERVATION COMMISSION

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified in the notice begins. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL	X		

Hobbs, New Mexico

Place

March 6, 1951

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the.....

The Ohio Oil Company

J. W. Grizzell

Well No. 2

in NW/4, SE/4

Company or Operator

Lease

of Sec. 5, T. 22S, R. 37E, N. M. P. M. Penrose-Skelly Field.

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

This well has been producing in Penrose-Skelly formation since October 1, 1937. The initial production was 24 bbls. in 24 hrs. Present production approximately 1 bbl. in 24 hrs. Following is a record of casing in the well:

9-5/8" OD 36# set @ 259'.

7" OD 24# set @ 3468'.

It is The Ohio Oil Company's intention to drill this well deeper to test the Drinkard Zone. Will case and cement off old pay zone from 3720 to 3750'. Company tools will be used from present depth 3750' to approximately 6500'. Approximately 3500' of 5 1/2" casing on top which will be run inside of old 7" casing. 5" extreme line casing will be used from 3500' to approximately 6500' and cemented to surface.

Approved....., 19.....
except at follows: MAR - 7 1951

The Ohio Oil Company

Company or Operator

By

J. B. Reese

Position

Assistant Superintendent

Send communications regarding well to

Name

The Ohio Oil Company

Address

Box 1607

Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Roy Yarbrough

Title

Oil Cons. Inspector