

STATE OF NEW MEXICO
OIL CONSERVATION COMMISSION



~~SANTA FE, NEW MEXICO~~

Box 522
Carlsbad, New Mexico
April 11, 1936

Landreth Production Corporation
Petroleum Building
Fort Worth, Texas

Gentlemen:

I am returning herewith form C-101, "Notice of Intention to Drill" your J. W. Grizzell Well No. 1, in the SW₄ of Sec. 5, T. 22 S., R. 37 E., to be signed and also for the casing program to be corrected.

The casing program for this area is as follows: The surface pipe shall be set at least 15 feet into the red beds and cemented to the surface. The production string of casing shall be set either on the top or within the producing zone. Where no intermediate string is used the production string shall be cemented with 150% of the calculated amount required to fill back to bottom of cellar. Or a two-stage cement job may be used, the lower stage shall be cemented with at least that amount of cement which would theoretically bring the cement 200 feet above the casing shoe. The upper stage shall cement the string from just below the top of the salt to the surface, using 150% of the calculated amount.

Very truly yours,

F. L. Vesely,
State Oil & Gas Inspector.

FJV:t

Encls.

*Frank?
Harden say delay in answering,
have been away several days -
have signed forms and shown amount
of 7" casing to be set. This is
a combination Rotary & Cable Tool drill.
Regards,
Further*

FILE