## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

ne Atlar	ntic Refi	Company or On	- Earl Grissel erator Lease	<u>1</u> we	ell No. 1 i	
Sec. 6	, T. 22	8 R 37 E		enrose	Field,Lea	County.
	N.	The well i	s 1980 feet	[X] [S.] of the_	north_line and	660feet
			of the cast			
		1 1	ion from section or o			
			d the oil and gas lea			
			land the owner is_			
						· · · · · · · · · · · · · · · · · · ·
	<del>                                     </del>		ent land the permitt			
	<del>- </del>   -					
_			is			
	40 400	Addross				
LOCATE W	640 ACRES ELL CORREC	CTLY We propose	e to drill well with			
	Cinc of	TIT -2 -14 To The				
	Size of Casing  12-1/2** 8-1/4** 5-1/2**	32 <del>#</del>	S.H.Lapweld S. H. SS	250° 1400°	Landed or Cemented	Surface 800
Hole  16 <sup>n</sup> 11-3/4 <sup>n</sup> 7-7/8 <sup>n</sup>	Casing  12-1/2** 8-1/4** 5-1/2**	50# 32# 17#	Second Hand S.H.Lapweld S. H. SS S.S.	250° 1400° 3800°	Cemented Cemented	Surface 800 800
Hole  16" 11-3/4" 7-7/8"  changes in the	Casing  12-1/2* 8-1/4* 5-1/2*  he above pla roductive oil	50# 32# 17#	Second Hand S.H.Lapweld S. H. SS	250° 1400° 3800°	Cemented  Comented  R  R  g or landing casin  feet.	Surface 800 800
Hole  16" 11-3/4" 7-7/8"  changes in that the first proditional information of the control of th	Casing  12-1/2* 8-1/4* 5-1/2*  he above pla roductive oil rmation:	50# 32# 17#	Second Hand  S.H.Lapweld  S. H. SS  S.S.  e we will notify you  d occur at a depth o	260° 1400° 3800°  1 before cementing f about 3800	Cemented  Cemented  n  g or landing casin  feet.	Surface 800 800
Hole  16" 11-3/4" 7-7/8"  changes in that the first proditional information of the control of th	Casing  12-1/2* 8-1/4* 5-1/2*  he above pla roductive oil rmation:	50# 32# 17# In become advisable or gas sand should	Second Hand  S.H.Lapweld  S. H. SS  S.S.  e we will notify you  d occur at a depth o	260° 1400° 3800°  1 before cementing about 3800  Sincerely yours, THE ATL	Cemented  Comented  R  R  g or landing casin  feet.	Surface 800 800
Hole  16" 11-3/4" 7-7/8"  changes in that the first pr	Casing  12-1/2* 8-1/4* 5-1/2*  he above pla roductive oil rmation:	50# 32# 17# In become advisable or gas sand should	Second Hand  S.H.Lapweld  S. H. SS  S.S.  e we will notify you  d occur at a depth o	260° 1400° 3800°  1 before cementing about 3800  Sincerely yours,  THE ATL  Co	Cemented  Comented  R  g or landing casin feet.  ANTIC REFINING mpany or Operator  Laggar	Cement Surface 800 800 g. We estimate
Hole  16" 11-3/4" 7-7/8"  changes in that the first proditional information of the control of th	Casing  12-1/2* 8-1/4* 5-1/2*  ne above pla roductive oil remation:	50# 32# 17#  In become advisable or gas sand should	Second Hand  S.H.Lapweld  S. H. SS  S.S.  e we will notify you doccur at a depth of the second Hand	260° 1400° 3800°  1 before cementing f about 3800  Sincerely yours,  THE ATL  Co By ATL  Position Petro	Cemented  Comented  R  R  g or landing casin feet.  ANTIC REFINING Impany or Operator  Lag grander  Class grand	Surface 800 800  g. We estimate  G. COMPANY
Hole  16" 11-3/4" 7-7/8"  changes in the at the first predictional information of the company of	Casing  12-1/2* 8-1/4* 5-1/2*  ne above pla roductive oil remation:	50# 32# 17# In become advisable or gas sand should	Second Hand  S.H.Lapweld  S. H. SS  S.S.  e we will notify you doccur at a depth of the second Hand	260° 1400° 3800°  1 before cementing f about 3800  Sincerely yours,  THE ATL  Co By ATL  Position Petro	Cemented  Comented  R  g or landing casin feet.  ANTIC REFINING mpany or Operator  Laggar	Surface 800 800  g. We estimate  GOUPANY