(Feb. 1651)	approvance miles in or see
	Las Cruces
(SUBMIT IN TRIPLICATE)	Land Once
UNITED STATES	Lesso No. 032573 - B
DEPARTMENT OF THE INTERIO	R ^{Unit}
GEOLOGICAL SURVEY	
SUNDRY NOTICES AND REPORTS	ON WELLS, new Merico
NOTICE OF INTENTION TO DRILL SUBSEQUENT REPORT OF W	WATER SHUT-OFF
	SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	ALTERING CASING
	RE-DRILLING OR REPAIR
	ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	STORY
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR C	OTHER DATA)
Elliott	il 6, 19. <u>54</u>
Well No is located <u>660</u> ft. from ${N \\ S}$ line and <u>1980</u> ft	
	()
Strik SE 6 22S 37E NMPM (% Sec. and Sec. No.) (Twp.) (Range) (Meridia	an)
Penrose-Skelly Lea (Field) (County or Subdivision)	(State or Territory)
State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed work) On March 3 we ran 9 sacks of cement which plugged	
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a A	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a A	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a A	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a A	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a A	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and I understand that this plan of work must receive approval in writing by the Geological Survey Company <u>Carper Drilling Company</u> , Inc.	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
Cn March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and I understand that this plan of work must receive approval in writing by the Geological Survey Company <u>Carper Drilling Company</u> , Inc.	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and I understand that this plan of work must receive approval in writing by the Geological Survey Company <u>Carper Drilling Company</u> , Inc.	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
Cn March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and I understand that this plan of work must receive approval in writing by the Geological Survey Company <u>Carper Drilling Company</u> , Inc.	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-2 mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and I understand that this plan of work must receive approval in writing by the Geological Survey Company <u>Carper Drilling Company</u> , Inc. Address <u>Artesia</u> , New Mexico By	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi we ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and contain was cleaned and leveled April 2, 1954 and Company	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi we ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and contain was cleaned and leveled April 2, 1954 and Company	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi we ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and contain was cleaned and leveled April 2, 1954 and Company	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and location was cleaned and leveled April 2, 1954 and Company <u>Carper Drilling Company</u> , Inc. Address <u>Carper Building</u> <u>Artesia, New Mexico</u> <u>By Title Vice</u>	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.
On March 3 we ran 9 sacks of cement which plugged back to 3695'. We then dumped enough gravel to fi We ran a 3 sack cement plug. The casing was then with E-Z mix mud. We cemented the top and set a 4 location was cleaned and leveled April 2, 1954 and Company	the hole from 3771' ill back to 3530' where filled to the surface 4" standard marker. The d is now ready for inspection.