


N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD




AREA 640 ACRES  
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

NEVILLE G. PENROSE, INC.

Fort Worth, Texas

Company or Operator

Address

Well No. 6 in SW 1/4 of Sec. 7, T. 22 S. R. 37 E. N. M. P. M. Penrose Field, Lee County.

Well is 330 feet North of the 330 line and 330 feet West of the 1000 line of 1000.

If State land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is Charles S. Alves, Address Kansas City, Mo

If Government land the permittee is \_\_\_\_\_, Address \_\_\_\_\_

The Lessee is Neville G. Penrose, Inc., Address \_\_\_\_\_

Drilling commenced 1-9-40 19\_\_\_\_ Drilling was completed 1-23 19 40

Name of drilling contractor Ronan Drilling Co., Address Fort Worth, Texas

Elevation above sea level at top of casing 3445 feet.

The information given is to be kept confidential until \_\_\_\_\_ 19\_\_\_\_.

## OIL SANDS OR ZONES

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_

No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet.

No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet.

No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet.

No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	28	8	J&L	515	Baker				
5 1/2	14	8	"	3647	"				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8	300	125	Halliburton		
	5 1/2	3647	350	"		

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_

Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
			none			

Results of shooting or chemical treatment \_\_\_\_\_

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from top feet to bottom feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## PRODUCTION

Put to producing February 1 19 40

The production of the first 24 hours was 82 bbls. per hour natural  
barrels of fluid of which 100 % was oil; \_\_\_\_\_ %  
emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be \_\_\_\_\_

If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_

Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

John Civelier, Driller J. T. Klingler, Driller

Ralph Dougherty, Driller \_\_\_\_\_, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3rdday of February 19 40Eunice E. Craft  
Notary PublicMy Commission expires 6-1-40

Fort Worth, Texas

Place Date

Name J. M. BuchananPosition SecretaryRepresenting NEVILLE G. PENROSE, INC.  
Company or OperatorAddress Fort Worth, Texas.

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	15		Cellar
15	130		Sand and Caliche
130	380		Sand & Red Bed
380	1072		Red Bed, Red Rock & Shells
1072	1190		Anhydrite
1190	2450		Salt and Anhydrite
2450	2982		Anhydrite
2982	3332		Lime and Anhydrite
3332	3740	TD	Lime