

C. P. FALBY A NO. 2 HISTORY

660 FNL and 660 FWL
Section 8, T22S, R37E
Lea County, New Mexico

- October 19, 1937- 13", 40#, Lapweld casing set at 209' with 200 sacks of cement.
- October 22, 1937- Ran and set 9 5/8", 40#, Seamless casing at 1190' with 600 sacks.
- November 4, 1937- Ran and set 7", 24#, Seamless casing at 3500' with 300 sacks of cement. Total Depth 3760'.
- December 11, 1937- Acidized open hole 3500' - 3760' with 2000 gallons. The acid job resulted in a production of 134 BOPD and 12 BWPD.
- December 16, 1937- Shot open hole with 450 quarts of nitro-glycerin from 3584' - 3760'. The stimulation resulted a production of 76 BOPD flowing.
- April 11, 1989- Additionally completed into the Eumont Yates Seven Rivers Queen at 2610'-2970'. Perforated this interval with 48 shots. Acidized this interval with 4000 gallons of 15% HCL pumped at 3-6 BPM. Fracture treated the interval with 32,000 gallons of gelled water carrying 90,000 lbs. of 20/40 sand. Placed well on production in the Eumont Yates Seven Rivers Queen Formation to test production and apply for downhole commingling.