

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See ot
struction
reveler

Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

LC-033706 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C.P. Falby 'A' Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Drinkard

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 8, T-22-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1a. TYPE OF WELL:

OIL WELL ☒

GAS WELL ☐

DRY ☐

Other

b. TYPE OF COMPLETION:

NEW WELL ☐

WORK OVER ☒

DEEP-EN ☐

PLUG BACK ☐

DIFF. RESVR. ☐

Other

Abandoned Blinebry

Recompl. Drinkard

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1980' FNL & 1982' FWL of Sec. 8, T-22-S, R-37-E,
Lea County, New Mexico

At top prod. interval reported below

At total depth

14. PERMIT NO.

Regular

DATE ISSUED

-

15. DATE SPUDDED

7-20-38

16. DATE T.D. REACHED

8-18-38

17. DATE COMPL. (Ready to prod.)

Drinkard - 3-22-77

18. ELEVATIONS (DF, REB, RT, GR, ETC.)*

3432' (DF)

19. ELEV. CASINGHEAD

3422'

20. TOTAL DEPTH, MD & TVD

6557'

21. PLUG, BACK T.D., MD & TVD

6555'

22. IF MULTIPLE COMPL., HOW MANY*

-

23. INTERVALS DRILLED BY

0-6557'

ROTARY TOOLS

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

Perforate 5-1/2" OD csg w/2 JSPF @ 6343', 49', 51', 53', 63', 98', 6409', 12', 20', 26', 47' & 6457' (Old Drk. Perforations 6480-6555')

25. WAS DIRECTIONAL SURVEY MADE

-

26. TYPE ELECTRIC AND OTHER LOGS RUN

-

27. WAS WELL CORED

-

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
10-3/4"	32.75#	373'	12-1/4"	300	-0-
7"	24#	3514'	8-3/4"	300	-0-
5-1/2"	13#	6557'	6-1/4"	300	-0-

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PERFORATION RECORD (Interval, size and number)

Perforate 5-1/2" OD csg w/2 JSPF @ 6343', 49', 51', 53', 63', 98', 6409', 12', 20', 26', 47', & 6457' (Old perfs. 6480-6555').

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6343'-6555	1500 gals. 15% NE acid
	Frac w/21,714 gal. gelled
	Brine containing 17,718# 20/40 Sand

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
3-22-77		Pumping - 1-1/2" Beam Type				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
3-22-77	24	-	→	16	80	12	5000
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
-	-	→	16	80	12	37.8	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold

TEST WITNESSED BY

F. M. Reynolds

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Asst. Dist. Supt.

DATE

3-23-77

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 12: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS, AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Sand, Caliche, Red Rock	-0-	160	Total Depth 6557'	Blinbry Drinkard	532' 6343'	
Red Rock & Shells	160	320	PBTD			
Red Rock	320	380				
Red Bed	380	1100				
Red Rock & Anhydrite	1100	1275				
Anhydrite & Salt	1275	2450				
Anhydrite & Gypsum	2450	2515				
Anhydrite & Lime	2515	2748				
Lime	2748	4128				
Lime & Sand	4128	4194				
Lime	4194	4693				
Lime & Sand	4693	4726				
Lime	4726	4820				
Sand	4820	4880				
Sandy Lime	4880	4990				
Lime	4990	5024				
Sandy Lime	5024	5259				
Lime	5259	6557				