

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See ot.
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

LC-033706(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C.P. Falby "A" Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Blincy

11. SEC., T. R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 8, T-22-S, R-37-E

12. COUNTY OR
PARISH

Lea

13. STATE

New Mexico

1a. TYPE OF WELL:

OIL WELL ☒ GAS WELL ☐ DRY ☐ Other

b. TYPE OF COMPLETION:

NEW WELL ☐ WORK OVER ☒ DEEP-EN ☐ PLUG BACK ☒ DIFF. RESVR. ☐ Other

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Well is located 1980' from the North line and 1982' from the West line of Section 8, T-22-S, R-37-E, Unit Letter F.

At top prod. interval reported below

At total depth

14. PERMIT NO.

Regular

DATE ISSUED

June 18, 1971

15. DATE SPUDDED

7-20-38

16. DATE T.D. REACHED

8-14-38

17. DATE COMPL. (Ready to prod.)

8-18-38

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3432' DF

19. ELEV. CASINGHEAD

3419'

20. TOTAL DEPTH, MD & TVD

6557'

21. PLUG, BACK T.D., MD & TVD

6392'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

6557'

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 1 JSPI @ 5532', 34', 44', 46', 54', 97', 99', 5630', 43', 57', 70', 72', 94', 5703', 17', 25', 27', 38', 40', 53', 55', 60', 62', 98', 5800', 30', 50', 60', 68', 75', 91', 5923', 29', 37' and 39'.

25. WAS DIRECTIONAL
SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN

37' and 39'.

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
NO CHANGE					

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	5875'	

31. PERFORATION RECORD (Interval, size and number)

1 JSPI @ 5532', 34', 44', 46', 54', 97', 99', 5630', 43', 57', 70', 72', 94', 5703', 17', 25', 27', 38', 40', 53', 55', 60', 62', 98', 5800', 30', 50', 60', 68', 75', 91', 5923', 29', 37' and 39'.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5532' - 5939'	Acidize w/1800 gals 15% HF acid. Frac w/30,000 gals gelled lease crude w/1# 20/40 sand and 1/40# Adomite per gal.

33.* PRODUCTION

DATE FIRST PRODUCTION July 17, 1971		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing				WELL STATUS (Producing or shut-in) Flowing	
DATE OF TEST 7-17-71	HOURS TESTED 24	CHOKE SIZE 20/64	PROD'N. FOR TEST PERIOD →	OIL—BBL. 38	GAS—MCF. 410	WATER—BBL. 33	GAS-OIL RATIO 10800
FLOW. TUBING PRESS. 150	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL. 38	GAS—MCF. 410	WATER—BBL. 33	OIL GRAVITY-API (CORR.) 39	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold - Skelly Oil Company

TEST WITNESSED BY

B. C. O'Kief

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

Assistant District

SIGNED

TITLE

Superintendent

DATE

July 26, 1971

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22 and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
NO CHANGE				NO CHANGE		

RECEIVED

AUG 5 1971
OIL CONSERVATION COMM.
HOODS. H. H.