

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Humble Oil And Refining Co.

P.O. Box 2180, Houston, Texas

Company or Operator

Address

J. L. Greenwood

Well No. 10

in SE 1/4

of Sec. 9

T. -22-S

Lease

R. -37-E

N. M. P. M.

Brunson

Field,

Lea, New Mexico

County.

Well is 660 feet south of the North line and 760 feet west of the East line of SE 1/4, Sec. 9

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is J. L. Greenwood Address Eunice N. M.

If Government land the permittee is Address

The Lessee is Humble Oil And Refining Co. Address Houston, Texas

Drilling commenced March 21, 1947 19 Drilling was completed May 4, 1947 19

Name of drilling contractor McQueen & Clevenger Address Ft. Worth, Texas

Elevation above sea level at top of casing 3428 feet

The information given is to be kept confidential until None 19

OIL SANDS OR ZONES

No. 1, from 7618 to Ellenburger No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	SET & STAM FROM	PERFORATED		PURPOSE
							FROM	TO	
10 3/4"	40.50	8-R	Rep.	257.94	Hall.				
"	32.75	8-R	Smith	120.74	"				
7 5/8"	26.40	8-R	Natl.	2779.45	"				
5 1/2"	17.00	8-R	"	1335.42	"				
"	15.5	8-R	"	3075.59	"				
"	14.00	8-R	"	3285.49	"		7642 7660	7653 7692	Pay Zone "

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	10 3/4"	392.18	300	Hall.		
9 7/8"	7 5/8"	2792.95	1100	"		
6 3/4"	5 1/2"	7710.00	700	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHILL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Western 15# L.T.	2000	5-9-47	7642 - 7653 7660 - 7692	

Results of shooting or chemical treatment Satisfactory

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 7711 feet and from feet to feet
Cable tools were used from feet to feet and from feet to feet

PRODUCTION

Put to producing May 14, 1947 19
The production of the first 24 hours was 780 barrels of fluid of which PLO % was oil: %
emulsion; % water; and % sediment. Gravity, Be 41.2
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in. Tubing Pressure 310# Casing Pressure 0#

EMPLOYEES

R. L. Martin Driller Wayne Ballow Driller
Tom Childress Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 24th

at Dallas, Texas on May 25, 1947

day of May, 1947

Name

Position Division Chief Clerk

Representing Humble Oil And Refining Company

My Commission expires 5-1-47

Address Box 1400, Dallas, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	375		Surface
375	400		Surface and Red Bed
400	1060		Red Bed
1060	1180		Anhy.
1180	1325		Salt and Anhy.
1325	1800		Anhy. and Salt
1800	2172		Salt, Anhy. and shells
2172	2350		Anhy., Salt
2350	3015		Anhy.
3015	3170		Anhy. Lime
3170	3378		Anhy.
3378	3525		Anhy. Lime
3525	7307		Lime
7307	7372		Lime and Shale
7372	7383		Lime
7383	7551		Lime and Shale
7551	7563		Shale and Streaks Lime
7563	7590		Shale Lime
7590	7610		Lime Shale
7610	7634		Lime and streaks of Shale
7634	7671		Lime Shale
7671	7702		Lime
7702	7711		Granite
	T.D.		