

DISTRICT I

1625 N. French, Hobbs, NM 88240

DISTRICT II

811 South First, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
3002510134

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

Fee

7. Lease Name or Unit Agreement Name

J L. Greenwood

8. Well No.

13

9. Pool name or Wildcat

Wantz-Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Exxon Corp.

3. Address of Operator **Regulatory Affairs**

P. O. Box 4358 Houston Tx 77210-4358

4. Well Location

Unit Letter **L** : **1980** Feet From The **South** Line and **990** Feet From The **West** line

Section **9** Township **22S** Range **37E** NMPH **Lea** County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3114' DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: _____ ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG & ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: _____ ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/28/99 Squeeze Blinbry Perfs (4637-5812) w/100 sx cmnt.

6/01/99 Tag sand @ 5853, washed down to 6028, drill out CIBP to 6559.

6/02/99 Test squeeze Drinkard Perfs - OK. Squeeze Tubb perfs (6083-6110) w/100 sx Cl C cmnt.

6/04/99 Drill out CIBP's at 6559 and 7105.

6/05/99 Set CIBP @ 7155, perf 7022-7030; 7046-7051; 7082-7100 - 1 spf, 31 total shots. Dumped 20' cmnt on top of plug. Tested casing - bad.

6/09/99 Set CIBP @ 7080 w/20' cmnt on top of plug. Perfed 6710-6744; 6762-6766; 6822-6831; 6858-6868 1 spf, 57 spf. Tested OK.

6/10/99 Acidize w/57 bbls 20% HCL and 114 1.3 SG Ball Sealers.

6/11/99 Pumped 516 sx 20/40 Ottawa sand Avg. 33 BPM @ 6400 psi

6/16/99 Tagged sand @ 6493, circulate sand out and down to 6960'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Allison Myrow TITLE **Staff Office Assistant**

DATE **08/04/1999**

TYPE OR PRINT NAME **Allison Myrow**

TELEPHONE NO. **(713) 431-1213**

(This space for State Use)

ORIGINAL SIGNED BY CHRIS WILLIAMS

APPROVED BY DISTRICT I SUPERVISOR

TITLE _____

DATE **NOV 16 1999**

CONDITIONS OF APPROVAL IF ANY:

Handwritten notes and signatures at the bottom of the page, including "JL", "20 R1", "P46", and a large signature.