

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)November 23, 1960
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Secony Mobil Oil Company, Inc. Brumson-Argo Well No. 1 in B
(Company or Operator) Lessee (Unit)
NW $\frac{1}{4}$ NE $\frac{1}{4}$ of Sec. 9, T. 22S, R. 37E, NMPM, Blinbry & Tubb Pool
(40-acre Subdivision)
Lea County.

TD: 6569'

FULL DETAILS OF PROPOSED PLAN OF WORK

PBD: 6454'

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Perfs: Blinbry: 5505-5523, 5536-5566, 5706-5724, 5748-5764, 5778-5788; Tubb: 5973-5981, 5987-5996, 6015-6020, 6133-6180

CIBP @ 5810' & 6045'

Packer @ 6108.

5" Csg, 15# XL, Set @ 6569', Top cement @ 2700'.

Kill well w/Lse crude. Pull 2" tbg. Run 2" tbg & HW Pkr to 5650' & swab to test perfs 5706-5724, 5748-5764 & 5778-5788. If perfs test wtr or dry, pull tbg & pkr & run 2" tbg & EM Retainer to 5650' & squeeze perfs w/100 sks cement. Run 2" tbg, 3 - 3 $\frac{1}{4}$ " DC & 4 $\frac{1}{8}$ " bit & drill out to 6030' w/Lse crude. Run 2" tbg & pkr to 5950' & swab test perfs 5973-6020 (3 sets). If swab dry squeeze perfs w/100 sks cement. Pull tbg & pkr. Run 2" tbg, 3 - 3 $\frac{1}{4}$ " DC & 4 $\frac{1}{4}$ " bit & drill out to 6250'. Pull tbg, DC & bit. Run 2 $\frac{1}{2}$ " tbg, BP & pkr to 6100' & swab test perfs @ 6133-6180' w/BP set @ 6200' w/10' sand on top. Perf thru tbg @ 6112', 6102', 6090' & 6054' w/4 JSPP. Re-set BP @ 6125' & with pkr @ 6035', swab to test perfs 6054'-6112'. Frac w/20000 gals lse crude + 12 rubber ball sealers + 1/20# adomite + 1# sand per gal. Swab test Tubb Zone. Kill Tubb Zone w/Lse crude. Pick up BP & set @ 5600'.

Approved....., 19.....
Except as follows:Secony Mobil Oil Company, Inc.
Company or OperatorBy D. H. SamplesPosition District Producing Superintendent
Send Communications regarding well to:Approved
OIL CONSERVATION COMMISSIONBy [Signature]Name Secony Mobil Oil Company, Inc.Title [Signature]Address Box 2406, Hobbs, New Mexico